



# Kinetic evaluation of simultaneous waste cooking oil hydrolysis and reactive liquid-liquid Cu extraction from synthetic Cu-containing wastewater: Effect of various co-contaminants



Lu Ki Ong<sup>a</sup>, Phuong Lan Tran Nguyen<sup>b</sup>, Felycia Edi Soetaredjo<sup>c</sup>, Suryadi Ismadji<sup>a,c,\*</sup>, Yi-Hsu Ju<sup>a,\*\*</sup>

<sup>a</sup> Department of Chemical Engineering, National Taiwan University of Science and Technology, 43, Keelung Rd., Sec. 4, Taipei 10607, Taiwan

<sup>b</sup> Department of Mechanical Engineering, Can Tho University, 3-2 Street, Can Tho City, Viet Nam

<sup>c</sup> Department of Chemical Engineering, Widya Mandala Surabaya Catholic University, Kalijudan 37, Surabaya, Indonesia

## ARTICLE INFO

### Article history:

Received 24 March 2017

Received in revised form 14 June 2017

Accepted 17 June 2017

Available online 21 June 2017

### Keywords:

Hydrolysis

Wastewater reuse

Liquid-liquid extraction

Heavy metal

Waste cooking oil

Fatty acids

Subcritical water

## ABSTRACT

Combination of oil hydrolysis reaction and reactive liquid-liquid extraction of Cu<sup>2+</sup> from wastewater offers economic and environmental advantage than running two processes separately. To give better insight on the application of the proposed process to treat real wastewater, the effects of other pollutants (acid/base, chelating agents, organic solvent, anions) present in the synthetic Cu-containing wastewater were studied. The reaction was carried out in a batch reactor using a water/acylglycerides molar ratio of 30:1 at 225 °C up to 8 h to understand the effect of the studied parameters during the reaction time course. It was found that pH influenced acid/base balance, which governs catalysis and Cu-soap formation in subcritical water. Chelating agents formed strong complexation with Cu<sup>2+</sup> that changed Cu removal mechanism from cation exchange reaction to that of conventional solvent extraction. The presence of organic solvents affected the dielectric constant of water that shifted the equilibrium of cation exchange reaction towards lipophilic Cu soap formation. Different anion type produced different type of acid by means of the cation exchange mechanism that influenced acid catalysis and Cu-soap formation. Other heavy metal cations expressed the same cation exchange mechanism and catalysis ability as that of Cu<sup>2+</sup>.

© 2017 Published by Elsevier B.V.

## 1. Introduction

Among all waters in the world, fresh water only occupies 2.8% with only around 0.63% available as potable surface and ground waters [1]. Based on that fact, fresh water is a very limited resource for the increasing global population. Wastewater reuse and recycling are one way to alleviate the water shortage issue. Reuse and recycle of wastewater require a good understanding on the composition and characteristics of wastewater.

Pollutants in wastewater are classified as organic and inorganic. Although both classes can impose certain level of hazard to the environment, a class of inorganic pollutants named heavy metals possess lethal toxicity and strong persistency to human, animals, and even microorganisms, which has to be removed before the

recycle and reuse of wastewater [2]. Various techniques are available for treating heavy metals in wastewater such as membrane filtration, solvent extraction, chemical precipitation, ion exchange, adsorption, and electrochemical deposition [3]. Nevertheless, all these methods are limited by some factors such as expensive capital cost, material fabrication, and material regeneration, which overall hinders its application for treating large volume of industrial wastewater [3,4].

Copper (Cu) is a heavy metal that commonly exists in wastewater from various industries such as printed circuit board, metal plating, battery manufacturing, electronic, mining, and metallurgical [3,5–7]. Moreover, the amount of Cu-containing wastewater generated is undoubtedly increasing with increasing production of electronics in this modern era. Other pollutants may exist in Cu-containing wastewater. For example, Fe, Zn and Ni may exist together with Cu in the drainage of acid-treatment of ores [8,9]. In the plating and printed circuit board manufacturing, chelating agent and organic solvents also are present [10]. The existence of those pollutants may inhibit the recovery and removal of Cu from the wastewater. Due to those contaminants, Cu removal was required to pass a series of treatments, such as pH-controlled

\* Corresponding author at: Department of Chemical Engineering, National Taiwan University of Science and Technology, 43, Keelung Rd., Sec. 4, Taipei 10607, Taiwan.

\*\* Corresponding author.

E-mail addresses: [suryadiismadji@yahoo.com](mailto:suryadiismadji@yahoo.com) (S. Ismadji), [yhju@mail.ntust.edu.tw](mailto:yhju@mail.ntust.edu.tw) (Y.-H. Ju).

solvent extraction with different carrier agent [11], a combined microbial desalination cells and electro-dialysis system [12], and combination of advanced oxidation-chemical precipitation [7,13] to remove each pollutant separately allowing Cu to be removed effectively.

Recently, a study reported the utilization of artificial Cu-containing wastewater for hydrolysis of waste cooking oil under subcritical water state, which offers a promising way to directly reuse wastewater [14]. Direct reuse of Cu-wastewater for waste cooking oil hydrolysis process also brings revenue by producing fatty acids (FAs) instead of simply remove  $\text{Cu}^{2+}$  and dispose the waste cooking oil. This strategy is critical to overcome the economic uncertainty in the realization of wastewater reuse [15]. Moreover, the process was demonstrated to possess remarkably higher Cu removal (5 times) from wastewater without adding carrier agent compared to the use of refined vegetable oil alone in the solvent extraction process, which reflected high aspect of economic and environmental sustainability [16]. In that study, free  $\text{Cu}^{2+}$  was described to undergo an exchange with two *in situ* generated FA molecules, producing a molecule of a mineral acid catalyst and Cu-soap, where the latter is soluble in the oil phase and provides a slight degree of water-in-oil emulsification. However, the use of artificial wastewater in the previous studies often did not cover the effects of other organic and/or inorganic compounds that co-exist with Cu ion in the wastewater [11,14]. Overlooking the presence of these compounds may surprisingly alter the Cu exchange mechanism and catalysis of oil hydrolysis reaction, hence leading to the rising of uncontrolled aspects when real wastewater is dealt with. In this study, the effect of possible co-contaminants in the Cu-containing wastewater, such as acid-base, chelating agent, organic solvents, and anion type on FA concentration and Cu removal percentage was thoroughly evaluated by kinetic modeling developed from the previously studied basic reaction mechanism. Different divalent heavy metals sulfate salts were also assessed to illustrate the utilization of a wider range of heavy metal-containing wastewaters.

## 2. Experimental

### 2.1. Chemicals

Waste cooking oil was donated by a local restaurant in Taipei, Taiwan. The oil was kept in a sealed amber glass bottle to avoid air oxidation. The oil was used without further pretreatment. KOH (85%, Acros Organics, USA) and HCl (37% purity, Acros Organics, USA) were used for pH adjustment and acid-base titration analysis. Anhydrous  $\text{CuSO}_4$  (97%, Shimakyu, Japan),  $\text{CuNO}_3 \cdot 3\text{H}_2\text{O}$  (99%, Acros Organics, USA),  $\text{CuCl}_2 \cdot 2\text{H}_2\text{O}$  (Sigma Aldrich, USA),  $\text{Cu}(\text{CH}_3\text{COO})_2 \cdot \text{H}_2\text{O}$  (J.T. Baker, USA),  $\text{FeSO}_4 \cdot 7\text{H}_2\text{O}$  (99%, Shimakyu, Japan),  $\text{NiSO}_4 \cdot 6\text{H}_2\text{O}$  (99%, Shimakyu, Japan),  $\text{ZnSO}_4 \cdot 7\text{H}_2\text{O}$  (99% Sigma Aldrich, USA),  $\text{H}_2\text{SO}_4$  (95–97%, Scharlau Chemical, Spain), ethanol (95%, Echo Chemical, Taiwan), and oxalic acid dihydrate ( $\geq 99\%$ , Kokusan Chemical Co. Ltd., Japan) were reagent grade. Analytical reagent grade anhydrous citric acid (99.5%, Acros Organics, USA) and anhydrous ethylenediaminetetraacetic acid (EDTA, 98.5%, Sigma Aldrich, USA) were used in the experiment on chelating agent effect. Acid-base titration indicator used was phenolphthalein (Sigma Aldrich, USA) dissolved in ethanol. All solutions were made by dissolving the corresponding salts with deionized water into a concentration of 25,000 mg metal (II)/kg.  $\text{HNO}_3$  (90%, May and Baker, UK) was diluted by deionized water to form 10% v/v solution for copper ion extraction from the oil hydrolysate. A mixed standard solution (solution IV, 1000 mg/L, Merck Chemicals, USA) was used to obtain Cu, Fe, Ni, and Zn calibration curves in the inductively coupled plasma (ICP) measurement.

### 2.2. Waste cooking oil hydrolysis

A mixture of waste cooking oil and  $\text{CuSO}_4$  solution (500 mg  $\text{CuSO}_4/\text{kg}$  solution = 3.13 mmol  $\text{Cu}^{2+}/\text{L}$ , pH 5.0) with a triacylglycerides to water molar ratio of 1:30 was introduced into a stainless steel reactor. The reactor apparatus is comprised of a 200 mL glass chamber, a 316-grade stainless steel autoclave body, a K-type thermocouple, a PID temperature controller, a pressure gauge, a magnetic stirrer, and an external electric heater (Fig. S1). After the reactor was closed tightly, trapped air was purged out by nitrogen. The reactor was then heated to 225 °C and held at that temperature up to 8 h to reach equilibrium according to the previous study [14]. After the reaction, the reactor was cooled to 50 °C. Aqueous phase was separated prior to washing to remove trapped glycerol in the product for monitoring the change of aqueous pH. Washing step was carried out twice using warm deionized water. Separation was performed gravitationally in a separation funnel overnight. The recovered oil product was weighed and analyzed for its acid value (AV) and Cu content.

The effect of the initial pH of the copper solution was studied at pH 4.0 and 6.0 by addition of 0.1 N of  $\text{H}_2\text{SO}_4$  or KOH. Adjustment of pH by KOH was stopped at pH 6.0 to avoid Cu precipitation. EDTA and citric acid were introduced to the  $\text{CuSO}_4$  solution (1:1 molar ratio) at pH 3.0–9.0 to study the effect of chelating agent. Meanwhile, 0.25–1.0% aqueous ethanol or acetone solution was used to dissolve and dilute  $\text{CuSO}_4$  to obtain 500 mg  $\text{CuSO}_4/\text{kg}$  solution used in the experiments on the effect of organic solvents. Ethanol and acetone were picked as the model solvents in cleaning metals with the concentration simulated based on total organic carbon content of printed circuit board wastewater in other studies [7,10]. Anion type was evaluated by changing  $\text{CuSO}_4$  solution into  $\text{CuNO}_3$ ,  $\text{CuCl}_2$  or  $\text{Cu}(\text{CH}_3\text{COO})_2$  solution with an equimolar concentration of  $\text{Cu}^{2+}$  (3.13 mmol  $\text{Cu}^{2+}/\text{L}$ ). Fe, Zn, and Ni solutions (3.13 mmol metal (II) ions/L) were also used to substitute  $\text{CuSO}_4$  solution to study the effect of divalent metal types. Experiments involving different pH, chelating agents, organic solvents, anion, and other divalent metal cations were carried out at the same temperature and acylglycerides/water molar ratio. All experiments were performed in triplicate.

### 2.3. Oil analysis

AV was analyzed by KOH titration according to ASTM D1980-87 method and calculated by using Eq. (1).

$$\text{AV (mg KOH/g oil)} = \frac{V_{\text{KOH}} (\text{mL}) \times C_{\text{KOH}} (\text{N}) \times 56.1}{\text{wt. of sample (g)}} \quad (1)$$

Saponification value (SV) was determined titrimetrically (ASTM D5558-95) to know the maximum obtainable fatty acid from the waste cooking oil. SV was calculated by using Eq. (2).

$$\text{SV (mg KOH/g oil)} = \frac{V_{\text{HCl}} \text{ of blank} - \text{sample (mL)} \times N_{\text{HCl}} (\text{N}) \times 56.1}{\text{wt. of sample (g)}} \quad (2)$$

Ester value (EV) and average molecular weight of waste cooking oil ( $\text{MW}_{\text{av}}$ ) as pure triacylglycerides can be calculated from Eqs. (3) and (4), respectively.  $\text{MW}_{\text{av}}$  was used to estimate the amount of oil required to fulfill 30:1 water/triacylglycerides molar ratio.

$$\text{EV (mg KOH/g oil)} = \text{SV (mg KOH/g oil)} - \text{AV (mg KOH/g oil)} \quad (3)$$

$$\text{MW}_{\text{av}} = \frac{1000 \times 56.1 \times 3}{\text{EV}_{\text{oil feed}} (\text{mg KOH/g oil})} \quad (4)$$

To provide more detailed concentration profile of acylglycerides for kinetic evaluation purpose, gas chromatography (GC) analysis was carried out as described in the previous study [14]. The results were then used in Eqs. (5)–(8) to obtain average molecular weight of triacylglycerides (TG), diacylglycerides (DG), monoacylglycerides (MG), and free fatty acids (FA). SV was defined as the total theoretical amount of saponifiable FA and the identity of acylglycerides as the ester of glycerol (G) and FA.

$$\frac{SV \text{ (mg KOH/g oil)}}{MW_{\text{KOH}}} = 1000 \frac{\text{mg oil}}{\text{g oil}} \times \left( 3 \frac{\text{wt.\% TG}}{MW_{\text{TG}}} + 2 \frac{\text{wt.\% DG}}{MW_{\text{DG}}} + \frac{\text{wt.\% MG}}{MW_{\text{MG}}} + \frac{\text{wt.\% FA}}{MW_{\text{FA}}} \right) \quad (5)$$

$$MW_{\text{TG}} = MW_{\text{G}} + (3 \times MW_{\text{FA}}) - (3 \times MW_{\text{H}_2\text{O}}) \quad (6)$$

$$MW_{\text{DG}} = MW_{\text{G}} + (2 \times MW_{\text{FA}}) - (2 \times MW_{\text{H}_2\text{O}}) \quad (7)$$

$$MW_{\text{MG}} = MW_{\text{G}} + MW_{\text{FA}} - MW_{\text{H}_2\text{O}} \quad (8)$$

Analysis results revealed that waste cooking oil comprised  $84.1 \pm 1.27$  wt.% TG,  $9.25 \pm 0.67$  wt.% DG,  $0.29 \pm 0.03$  wt.% MG, and  $6.29 \pm 0.59$  wt.% FA with SV and AV of  $200.73 \pm 2.70$  and  $13.58 \pm 1.18$  mg KOH/g oil, respectively. Molecular weights obtained were 839.66, 590.47, 341.28, 267.21, and 595.96 g/mol for TG, DG, MG, FA, and  $\text{Cu}(\text{FA})_2$ , respectively.

The amount of metals transferred into the oil phase was determined by acid extraction as reported in a previous study with slight modification [17]. Oil sample (5 g) was mixed with 20 mL 10% (v/v)  $\text{HNO}_3$  at 60 °C for 4 h under magnetic stirring (500 rpm). After the extraction was finished, the mixture was left to separate. The oil layer was cooled in a refrigerator and then filtrated using a 5- $\mu\text{m}$  filter paper (Advantec Grade No. 2). Aqueous layer was analyzed by an ICP-AES (Horiba Jobin Yvon 2000-2). Metal removal percentage was expressed as number of metal ions transferred into the oil phase to total metal ions put in the reaction system as showed in Eq. (9).

$$\text{Removal (\%)} = \frac{\text{Metal}_{\text{oil product}} \text{ (mg/kg)} \times \text{m}_{\text{oil product}} \text{ (kg)} - \text{Metal}_{\text{oil feed}} \text{ (mg/kg)} \times \text{m}_{\text{oil feed}} \text{ (kg)}}{C_{\text{metal solution}} \text{ (mg metal cations/kg)} \times \text{m}_{\text{metal solution}} \text{ (kg)}} \times 100\% \quad (9)$$

#### 2.4. Kinetic modeling

In this study, several assumptions were made:

- Total volume of liquid water and oil was constant at the given temperature and pressure, which was the volume of the reaction system (V). Concentration of species was expressed as mol/L.
- Thermodynamic properties of metal solution can be approached by those of pure water.
- Density of oil and water were constant regardless of the transfer of glycerol and change of oil composition [18].
- Reaction between diffusing metal ions and FA as the ion exchanger is instantaneous [19]. The reaction of metal ions and FA can be described as  $\text{M}^{2+} + 2\text{FA} + 2\text{H}_2\text{O} \leftrightarrow \text{M}(\text{FA})_2 + 2\text{H}_3\text{O}^+$ , where M is the metal.

Density of oil (mixture of TG, DG, MG and FA) was approached by the density of mixture of triolein, diolein, monoolein and oleic acid, which was simulated by NRTL-Rackett model in Aspen Plus

8.8 (Aspen Technology Inc., 2015). Due to high resemblance between the measured densities of oil and oleic-oil mixture at 25 °C (0.919 g/mL vs. 0.908 g/mL), the density of the studied waste cooking oil was predicted to be 0.807 g/mL at 225 °C (Fig. S2). Properties of pure water at the working temperature and pressure (225 °C and 2.94 MPa), particularly specific volume of water and steam was estimated from online calculator provided by Moscow Power Engineering Institute [20]. Liquid mass fraction ( $\omega^l$ ) of the total amount of water introduced into the reactor ( $\hat{V}$ ) then can be found through calculations using Eqs. (10) and (12) [21].

$$\hat{V} \text{ (m}^3\text{/kg)} = \frac{(2 \times 10^{-4} - \frac{m_{\text{oil}}}{P_{\text{oil}}})}{m_{\text{aqueous}}} \quad (10)$$

$$\hat{V} \text{ (m}^3\text{/kg)} = \omega^v \cdot \hat{V}^v + (1 - \omega^v) \cdot \hat{V}^l \quad (11)$$

$$\omega^l = (1 - \omega^v) \quad (12)$$

where  $m_{\text{oil}}$  and  $m_{\text{aqueous}}$  are mass of oil and metal solution (assumed as pure water), respectively. Superscript v and l refer to the vapor and liquid phase of water in the reactor with a volume of  $2 \times 10^{-4} \text{ m}^3$ . For temperature and pressure used in the experiments, calculation showed that 95.24 wt.% of the aqueous phase remained as liquid.

Initially  $\text{H}_3\text{O}^+$  came from water self-ionization [22], unless the system was acidified by  $\text{H}_2\text{SO}_4$ . The added amount of  $\text{H}_3\text{O}^+$  in moles can be traced by the difference of pOH to normalize the effect of metal ions as Lewis acid in the original Cu solution. In terms of base addition, added  $\text{OH}^-$  appears to subtract the amount of  $\text{H}_3\text{O}^+$  from water self-ionization. Initial concentration of  $\text{H}_3\text{O}^+$  was calculated by Eq. (13)

$$[\text{H}_3\text{O}^+] = \frac{\frac{\text{added } \text{H}_3\text{O}^+}{V} + \sqrt{\frac{\text{added } \text{H}_3\text{O}^+}{V} + 4 \cdot K_{\text{W}}}}{2} - \frac{\text{added } \text{OH}^-}{V} \quad (13)$$

where  $[\text{H}_3\text{O}^+]$  and  $K_{\text{W}}$  are concentration of the liberated proton and the self-ionization constant of water, respectively.

Reaction rate equations can be expressed as follows:

$$\frac{d\text{TG}}{dt} = -k_{\text{TG}} \cdot \text{TG} \cdot \text{H}_2\text{O} + k_{-\text{TG}} \cdot \text{DG} \cdot \text{HFA} \quad (14)$$

$$\frac{d\text{DG}}{dt} = k_{\text{TG}} \cdot \text{TG} \cdot \text{H}_2\text{O} - k_{-\text{TG}} \cdot \text{DG} \cdot \text{FA} - k_{\text{DG}} \cdot \text{DG} \cdot \text{H}_2\text{O} + k_{-\text{DG}} \cdot \text{MG} \cdot \text{FA} \quad (15)$$

$$\frac{d\text{MG}}{dt} = k_{\text{DG}} \cdot \text{DG} \cdot \text{H}_2\text{O} - k_{-\text{DG}} \cdot \text{MG} \cdot \text{FA} - k_{\text{MG}} \cdot \text{MG} \cdot \text{H}_2\text{O} + k_{-\text{MG}} \cdot \text{G} \cdot \text{FA} \quad (16)$$

$$\frac{d\text{G}}{dt} = k_{\text{MG}} \cdot \text{MG} \cdot \text{H}_2\text{O} - k_{-\text{MG}} \cdot \text{G} \cdot \text{FA} \quad (17)$$

$$\frac{d\text{Cu}(\text{FA})_2}{dt} = \frac{1}{2} \cdot \frac{d\text{H}_3\text{O}^+}{dt} = - \frac{d\text{Cu}^{2+}}{dt} = k_{\text{Cu}} (\text{Cu}^{2+} - \text{Cu}_{\text{interface}}^{2+}) \quad (18)$$

$$\text{Cu}_{\text{interface}}^{2+} = \frac{\text{Cu}(\text{FA})_2 \cdot (\text{H}_3\text{O}^+)^2}{K_{\text{Cu}(\text{FA})_2} \cdot (\text{FA})^2 \cdot (\text{H}_2\text{O})^2} \quad (19)$$

$$-\frac{dH_2O}{dt} = \frac{dFA}{dt} = k_{TG} \cdot TG \cdot H_2O - k_{TG} \cdot DG \cdot HFA + k_{DG} \cdot DG \cdot H_2O - k_{DG} \cdot MG \cdot FA + k_{MG} \cdot MG \cdot H_2O - k_{MG} \cdot G \cdot FA - 2 \cdot k_{Cu} (Cu^{2+} - Cu_{interface}^{2+}) \quad (20)$$

These equations were numerically solved using Euler method programmed in Excel (Microsoft Office 2007) with a step size of 0.5 min. All hydrolysis rate constants (L/moles.min),  $Cu^{2+}$  mass transfer coefficient (1/min), and apparent equilibrium constant of Cu-soap formation (L/moles) were estimated by the assistance of Solver Add-In to minimize the objective function (OF).

$$OF = \sum_{i=1}^n \left( \frac{Y^{ex} - Y^{cal}}{Y^{ex}} \times 100 \right)^2 \quad (21)$$

where Y is the data of AV and metal removal percentage found by experiments (ex) and fitting (cal), which are Eqs. (22) and (23) using concentrations found in the simulation.

$$AV^{cal} \text{ (mg KOH/g)} = \frac{1000 \times FA \times MW_{KOH}}{FA \times MW_{FA} + MG \times MW_{MG} + DG \times MW_{DG} + TG \times MW_{TG} + Cu(FA)_2 \times MW_{Cu(FA)_2}} \quad (22)$$

$$\text{Removal}^{cal} \text{ (\%)} = 100 \times \left( 1 - \frac{Cu^{2+}(\text{at } t)}{Cu^{2+}(t=0)} \right) \quad (23)$$

### 3. Results and discussion

#### 3.1. Effect of pH

Acid and base addition enhanced the reaction rate of FA production as showed in Fig. 1. Regardless of considerable difference in the formed Cu-soap amount, FA concentration of acidic system was found as high as that in the alkalized Cu solution system, which suggests a unique catalysis by  $H_2SO_4$  produced in the ion exchange reaction rather than the Cu-soap. Production of  $H_2SO_4$  was confirmed in both acidified and alkalized system from the final pH of the aqueous phase (2.4–2.6). Since the stoichiometric ratio of water to the acylglycerides in the system are fixed in this study, FA concentration obtained at equilibrium in the acidified and alkalized system remained similar (approximately 170 mg KOH/g oil), which is also in agreement with the concept of catalysis, where the catalyst is unable to alter the reaction stoichiometry.


Addition of base to  $CuSO_4$  solution was not simply spiking up Cu removal percentage by eliminating the net amount of protons in the reaction system. This enhancement was observed at the early stage of reaction since the amount of KOH added was not enough to overcome the initial acidic species to form either K-soap or  $K_2SO_4$  from the reaction between FA or  $CuSO_4$ . Considering the effect of subcritical water, certain extent of  $OH^-$  from self-ionization of water may be stabilized by the  $K^+$  present in the system [23]. A previous study showed a possible formation of soap with FA in the oil phase, which is called acid soap [24]. Similar mechanism to the cation exchange reaction between  $Cu^{2+}$  and FA [25] may explain the subcritical water effect to cause KOH formation from  $K^+$ , which further transformed into K-soap in the presence of FA. K-soap tends to dissolve in the aqueous phase to form oil-in-water emulsion, which may help hydrolysis of non-polar compound such as TG.

Kinetic rate constants in Table 1 show higher TG transformation rate in the acidified and alkalized Cu solution system. The increase in the reverse reaction rate constant of MG hydrolysis indicates that acid and alkaline treatments are not selective towards FA formation. Remarkably high reverse reaction rate constant than that of the forward reaction can be explained by a lower water amount used in this study (oil:water = 2:1 v/v) than in the studies with a negligible reverse reaction that used oil:water = 1:1–1:4 v/v [26,27]. Although the molar amount of water was excessive, only certain excessive amount of water could sufficiently dilute the formed glycerol and gave an impression of no reverse reaction in the system. From the same theory on the presence of K-soap, a higher reverse MG hydrolysis rate in the base-added system was due to the better transfer of glycerol from the aqueous phase in addition to the non-selectivity of  $H_2SO_4$  catalysis.

**Table 1**

Kinetic rate constants of waste cooking oil hydrolysis using Cu solution with different initial pH.

Kinetic rate constant	Initial pH		
	4.0	5.0 (original Cu solution)	6.0
$k_{TG}$	$9.72 \times 10^{-4}$	$7.94 \times 10^{-4}$	$1.00 \times 10^{-3}$
$k_{DG}$	$9.98 \times 10^{-3}$	$9.98 \times 10^{-3}$	$9.98 \times 10^{-3}$
$k_{MG}$	$1.82 \times 10^{-3}$	$9.55 \times 10^{-4}$	$1.91 \times 10^{-3}$
$k_{TG}$	0	0	0
$k_{DG}$	0	0	0
$k_{MG}$	$9.90 \times 10^{-3}$	$7.94 \times 10^{-3}$	$1.05 \times 10^{-2}$
$K_{Cu(FA)_2}$	$1.66 \times 10^{-10}$	$2.16 \times 10^{-9}$	$2.93 \times 10^{-8}$
$K_{Cu}$	$3.80 \times 10^{-3}$	$3.74 \times 10^{-1}$	$5.69 \times 10^{-3}$



**Fig. 1.** Effect of initial pH of Cu solution on the (A) AV and (B) Cu removal percentage.

For  $\text{Cu}^{2+}$  mass transfer, acid/base addition inhibited mass transfer through the formation of dense ionic barrier with a larger decrease of magnitude for more organized barrier of  $\text{H}^+$  in acidified system. Although cation exchange equilibrium constant ( $K_{\text{Cu}(\text{FA})_2}$ ) is supposed to be independent of pH, it was found that the  $K_{\text{Cu}(\text{FA})_2}$  in alkalized system was higher than in acidified system. This indicates that the acquired constant is the apparent equilibrium constant. An investigation of the change in equilibrium constant resulted in surprisingly comparable results with initial pH difference, which is about  $10^{-1.11}$  and  $10^{1.13}$  for acid- and base-added system, respectively. This finding revealed a hidden mechanism involving  $\text{HSO}_4^-$ , a type of inorganic ligand that could inhibit ion exchange reaction. Accordingly, the possible reason for a higher apparent equilibrium constant in the alkalized system is the suppressed  $\text{SO}_4^{2-}$  protonation by KOH formed in subcritical water. Since K-soap formation also involved consumption of a proton from FA, the theory of ion exchange facilitation by K-soap is interchangeable with the prevention of  $\text{SO}_4^{2-}$  protonation.

### 3.2. Effect of chelating agent

Chelating agent stabilizes metal ions to be precipitated in water by hindering metal-hydroxide precipitate formation. In the electrodeless Cu-plating, chelation of Cu is mandatory since the pH of the bath has to be adjusted to 13.5 for the oxidation of formaldehyde to occur [28]. However, the presence of chelating agent leads to difficult heavy metal removal process since the stability of metal in wastewater becomes very high [29,30].

By observation, aqueous solution of Cu-EDTA and Cu-citric acid possessed an acidic pH of 3.0, which later changed into very slightly more acidic after reaction (pH 2.9–3.0). Interestingly, same pH value of 4.8 was observed in the aqueous phase of non-catalytic system (oil and water only) as well as Cu-EDTA and Cu-citric acid with an initial pH of 5.0–9.0. These indicate unchanging  $\text{H}^+$  concentration in the chelated-Cu system that further reflects different mechanism for Cu transportation. Rather than ion exchange mechanism, van der Waals interaction of carbon backbone of chelating agents with oil phase may facilitate Cu-complex extraction to the oil phase in the form of dimer or polymer [31,32]. Since Cu-EDTA could form polymeric structure, removal percentage of Cu-EDTA complex was higher than dimeric Cu-citrate complex (Fig. 2B). This finding changed the model of Cu removal into Eq. (24).

$$-\frac{d\text{Cu}_{\text{complex, aq}}}{dt} = k_{\text{Cu-complex}} (\text{Cu}_{\text{complex, aq}} - \text{Cu}_{\text{complex, lip}}) \quad (24)$$




Fig. 2. Effect of chelating agents on (A) FA yield and (B) Cu removal percentage in the Cu-catalyzed hydrolysis of waste cooking oil at 225 °C.

Cu-EDTA and Cu-citric acid complexes were found to be stable in subcritical water [33–35]. Hence, concentration of Cu-complex in the aqueous phase ( $\text{Cu}_{\text{complex, aq}}$ ) was assumed to be the same as  $\text{Cu}^{2+}$  introduced into the system. Although some  $\text{Cu}^{2+}$  seen in Fig. S3 for Cu-citric acid system was at pH 3.0, the assumption still may be valid at high reaction temperature due to the increase of chelating stability of Cu-citrate complex, which has endothermic nature [36]. Fitting was employed to find mass transfer rate ( $k_{\text{Cu-complex}}$ ) and maximum concentration of Cu complex in the oil phase ( $\text{Cu}_{\text{complex, lip}}$ ).

Surprisingly, FA concentration in the system with chelating agents was slightly higher than chelating agent-free system. With significantly lower Cu removal percentage, the results indicate that Cu complex also induced catalytic ability in the reaction system. Nevel [37] mentioned that metal complexes are able to catalyze the reaction as long as some coordination sites are free from the ligand blocking. Fully occupied structures of Cu complex with studied ligands are given in Fig. S4. Based on the speciation diagram in Fig. S3 [38,39], free coordination sites are available only at pH lower than 5.0 for Cu-EDTA system and in the whole studied pH range of this work (2.0–9.0) for Cu-citric acid complex. FAs deprotonation can provide slight acidification to pH 4.8 and possibly changed the Cu-complex species [40]. Moreover, exothermic nature of  $\text{Cu}[\text{EDTA}]^{2-}$  complex as the fully occupied coordination complex of Cu with EDTA indicates its less proportion under high hydrolysis temperature [36].

On the other hand, dihydrate bridged Cu-complex structure could improve water transportation into the oil phase besides improving complex stability in the water [31,32]. Both Cu-EDTA and Cu-citrate have the same capability to form hydrogen bonding, given that the ability comes from the metal ion nature and not the ligand. Double function of chelated-Cu as catalyst and water vehicle resulted in a comparable FA concentration in contrast to the combination of acid catalyst ( $\text{H}_2\text{SO}_4$ ) and  $\text{Cu}(\text{FA})_2$  as water-in-oil emulsifier in the free-chelating agent system [14] even with limited amount of chelated-Cu in the oil phase.

In contrast to the result of free-chelating agent system, chelated-Cu performed catalysis of TG hydrolysis better than  $\text{H}_2\text{SO}_4$  produced from ion exchange of  $\text{CuSO}_4$  and FA (Table 2). While catalysis of forward and reverse MG hydrolysis were comparable to those in the free-chelating agent system, chelated-Cu system showed a slower rate of DG hydrolysis due to steric hindrance contribution of the confined structures of chelated Cu. Mass transfer of chelated-Cu was faster than free  $\text{Cu}^{2+}$  due to its lipophilicity.

**Table 2**

Kinetic rate constants obtained from experimental data fitting of waste cooking oil hydrolysis using chelated Cu solution at an initial pH of 5.0.

Constants	Chelating agent	
	EDTA	Citric acid
$k_{TG}$	$9.94 \times 10^{-4}$	$1.07 \times 10^{-3}$
$k_{DG}$	$4.26 \times 10^{-3}$	$2.80 \times 10^{-3}$
$k_{MG}$	$9.38 \times 10^{-4}$	$9.38 \times 10^{-4}$
$k_{-TG}$	0	0
$k_{-DG}$	0	0
$k_{-MG}$	$7.99 \times 10^{-3}$	$8.20 \times 10^{-3}$
$k_{Cu-complex}$	$3.83 \times 10^{-2}$	$1.20 \times 10^{-1}$
$k_{Cu-complex, lip}$	$7.38 \times 10^{-4}$	$7.78 \times 10^{-4}$

Compared to Cu-citrate complex, Cu-EDTA showed slower transfer due to its larger molecular size. This also explains a smaller  $k_{TG}$  and a slightly lower saturation concentration of Cu-EDTA complex in EDTA system due to higher steric hindrance and larger spatial occupation of molecules in the oil phase.

The possibility of  $K^+$  involvement in catalysis as occurred in the base addition was evaluated in the system with a lower pH (Table S1 and Fig. S5). Similar values of  $k_{TG}$  and  $k_{MG}$  independent of pH indicate that K-soap did not form as significant as in the free-chelating agent system. Though the system also contained  $K^+$ , the presence of negative-charged Cu-complex should be considered as the counter ion that inhibited  $K^+$  from being free in the aqueous phase. By varying pH, mass transfer of Cu-complex into the oil phase increased gradually due to less charge density of complex formed and more  $K^+$  available to neutralize complex charge at higher pH. Saturation concentration values were approximately constant with pH change since the space is limited by the fixed oil mass (volume) only.

### 3.3. Effect of organic solvent

Organic solvent presents in wastewater may lower down the dielectric constant of water [41], which could affect the formation of Cu-soap [25]. The increase of obtained FA concentration and Cu removal was small since only very small amount of solvents was added. At a glance, Fig. 3 showed comparable effect of the presence of ethanol and acetone. At equilibrium, the effect of solvent concentration on FA production was negligible (Fig. S6). Meanwhile, negligible increase on Cu removal percentage was observed, except for ethanol system at concentrations of 0.75 and 1 wt.%. Thus, in

order to accentuate the effect of organic solvent presence, 1 wt.% solvent concentration was chosen for kinetic modeling.

Due to better association of ethanol than acetone in water by means of the hydroxide group of ethanol,  $Cu^{2+}$  mass transfer ( $k_{Cu}$ ) in aqueous ethanol is faster than that in water-acetone (Table 3). Lower polarity also slightly increased the apparent equilibrium constant of Cu-soap formation. Facilitated mixing between water and oil by solvents was obvious from higher  $k_{TG}$  than that of pure  $CuSO_4$  solution. More non-polar acetone might give certain interference on the interaction between water and acylglycerides as observed in the slightly lower  $k_{TG}$ ,  $k_{MG}$ , and  $k_{-MG}$  than ethanol and pristine Cu solution.

### 3.4. Effect of anion types


In the previous study, mineral acid was discussed as the main catalyst that increased FA yield significantly [14]. Thus, the anion species may also affect acid catalysis in subcritical water [25]. In this study, equimolar Cu systems with sulfate anion ( $SO_4^{2-}$ ) was compared with nitrate ( $NO_3^-$ ), chloride ( $Cl^-$ ), and acetate ( $CH_3COO^-$ ), which are commonly found anions coupling with Cu in the wastewater. Overall, comparable FA yield and Cu removal were achieved for all anion systems (Fig. 4). A pH decrease to 2.3–2.5 was observed in all systems, except for the equilibrium pH of the aqueous phase in Cu-acetate system, which reached 3.63 due to lower deprotonation of acetic acid.

As showed in Table 4, Cu-chloride surpassed the other anion systems in TG hydrolysis. Cu-acetate system was the least among all. In the meantime, Cu mass transfer increased in the following order: Cu-chloride, Cu-nitrate, Cu-sulfate, and Cu-acetate. Since

**Table 3**

Reaction rate constants of waste cooking hydrolysis using 500 mg  $CuSO_4$  in 1 kg of 1 wt.% aqueous ethanol and acetone.

Kinetic rate constant	Aqueous organic solvent	
	Ethanol (1 wt.%)	Acetone (1 wt.%)
$k_{TG}$	$9.36 \times 10^{-4}$	$9.34 \times 10^{-4}$
$k_{DG}$	$9.98 \times 10^{-3}$	$9.98 \times 10^{-3}$
$k_{MG}$	$9.55 \times 10^{-4}$	$9.16 \times 10^{-4}$
$k_{-TG}$	0	0
$k_{-DG}$	0	0
$k_{-MG}$	$7.94 \times 10^{-3}$	$7.25 \times 10^{-3}$
$k_{Cu(FA)2}$	$2.80 \times 10^{-9}$	$2.81 \times 10^{-9}$
$k_{Cu}$	$3.83 \times 10^{-1}$	$3.69 \times 10^{-1}$



**Fig. 3.** Kinetic curves of (A) AV and (B) Cu removal percentage in the experiments using Cu solution contaminated with organic solvent.




Fig. 4. FA yield and Cu removal percentage in the hydrolysis of waste cooking oil using various anion types.

**Table 4**  
Reaction rate constants of waste cooking hydrolysis using Cu solution with different anion type.

Kinetic rate constant	Anion			
	Acetate	Chloride	Nitrate	Sulfate
$k_{TG}$	$7.34 \times 10^{-4}$	$8.24 \times 10^{-4}$	$8.04 \times 10^{-4}$	$7.94 \times 10^{-4}$
$k_{DG}$	$9.58 \times 10^{-3}$	$9.99 \times 10^{-3}$	$9.98 \times 10^{-3}$	$9.98 \times 10^{-3}$
$k_{MG}$	$8.65 \times 10^{-4}$	$9.84 \times 10^{-4}$	$9.55 \times 10^{-4}$	$9.55 \times 10^{-4}$
$k_{-TG}$	0	0	0	0
$k_{-DG}$	0	0	0	0
$k_{-MG}$	$7.62 \times 10^{-3}$	$8.01 \times 10^{-3}$	$7.91 \times 10^{-3}$	$7.94 \times 10^{-3}$
$K_{Cu(FA)_2}$	$2.16 \times 10^{-9}$	$2.16 \times 10^{-9}$	$2.16 \times 10^{-9}$	$2.16 \times 10^{-9}$
$K_{Cu}$	$3.75 \times 10^{-1}$	$3.64 \times 10^{-1}$	$3.68 \times 10^{-1}$	$3.74 \times 10^{-1}$

an equimolar amount of Cu should produce the same amount of proton, this trend may be the results of the acids dissociation at higher temperature. Negative logarithm of the acid dissociation constant ( $pK_a$ ) and the enthalpy of acid dissociation are listed in Table S2 [42–44]. HCl as the strongest acid demonstrated the highest hydrolysis rate constants among all acids formed in this study. As the weakest acid, acetic acid gave the lowest forward hydrolysis rate and the least inhibition of  $Cu^{2+}$  mass transfer by less ionic barrier made of hydrogen proton. In contrast with  $HNO_3$ , sulfuric acid has a smaller amount of proton since dissociation occurs in two steps with considerable weak dissociation at the second step (dissociation of  $HSO_4^-$ ). With exothermic nature,  $HSO_4^-$

is less deprotonated at high temperature by van't Hoff correlation, which also proved its inhibiting effect on ion exchange reaction in acidified system. The same apparent equilibrium constants indicate the same degree of cation exchange. With unselective nature of the acid catalyst, faster reversible reaction rate of MG hydrolysis was also observed at higher acidity.

### 3.5. Application of other divalent heavy metal ions

Substitution of  $CuSO_4$  by other heavy metal sulfate salts at the same initial metal concentration showed the same equilibrium FA concentration (Fig. 5). Same low equilibrium aqueous phase




Fig. 5. Kinetic curves of AV and removal percentage in the waste cooking hydrolysis using various metal sulfate solution (3.13 mmol metal (II) ions/L, initial pH 5.0).

**Table 5**

Kinetic rate constants obtained from the hydrolysis experiments using various metal sulfate solution (3.13 mmol metal (II) ions/L, initial pH 5.0).

Kinetic rate constants	Metal (II) cation			
	Zn	Fe	Ni	Cu
$k_{TG}$	$7.53 \times 10^{-4}$	$7.89 \times 10^{-4}$	$9.31 \times 10^{-4}$	$7.94 \times 10^{-4}$
$k_{DG}$	$9.68 \times 10^{-3}$	$9.98 \times 10^{-3}$	$9.99 \times 10^{-3}$	$9.98 \times 10^{-3}$
$k_{MG}$	$8.65 \times 10^{-4}$	$9.46 \times 10^{-4}$	$9.24 \times 10^{-4}$	$9.55 \times 10^{-4}$
$k_{-TG}$	0	0	0	0
$k_{-DG}$	0	0	0	0
$k_{-MG}$	$6.75 \times 10^{-3}$	$7.82 \times 10^{-3}$	$7.62 \times 10^{-3}$	$7.94 \times 10^{-3}$
$K_{Cu(FA)2}$	$2.16 \times 10^{-9}$	$5.81 \times 10^{-9}$	$3.59 \times 10^{-9}$	$2.16 \times 10^{-9}$
$k_{Cu}$	$1.55 \times 10^{-1}$	$2.04 \times 10^{-1}$	$4.35 \times 10^{-1}$	$3.74 \times 10^{-1}$

pH, all metals followed the same mechanism and sufficient catalyst was present in all systems. From the hydrolysis rate constants (Table 5), Ni gave the highest acylglycerides conversion. However, considering the same order of magnitude, all metals actually performed quite similar, indicating lower contribution of metal ions and soaps as catalyst species than the produced  $H_2SO_4$ .

Apparent equilibrium constants revealed the order similar to the Irving-Williams series:  $Cu \leq Zn < Ni < Fe$ , which also serves as a trend of Lewis acidity [45]. Higher Lewis acidity results in less cation exchange due to more solid hydration cage between metal ions and water ligand. However, since the acidity of metal ions is not as strong as the proton from the acid deprotonation, the magnitude of the constants remained similar. In the meantime,  $Cu^{2+}$  mass transfer coefficient increased with increasing electronegativity:  $Ni (1.91) > Cu (1.9) > Fe (1.83) > Zn (1.65)$ . This reflects metal ions attraction towards a free electron pair of species in the oil phase, either oxygen atom of the ester group in acylglycerides or oxygen atom of the deprotonated FA. Coincidentally, increasing TG hydrolysis rates were also showed by the same electronegativity trend. As the miscibility of acylglycerides in water increases as in the case of DG and MG, this trend is diminished by overshadowing catalysis of  $H_3O^+$ .

#### 4. Conclusion

The effects of other contaminants in the Cu-containing wastewater on the hydrolysis of waste cooking oil were studied. Overall, the presence of contaminants did not give significant effect on the FA production. However, system acidification and chelating agents remarkably lowered down Cu removal percentage. More ionic species by acid and base addition disturbed  $Cu^{2+}$  transfer from aqueous to oil phase by providing ionic barrier at the interface. Subcritical water effect particularly self-dissociation of water molecules had a certain contribution to the enhancement of hydrolysis in the acidified and alkalized system. Molecular interaction between the organic solvent and water influenced the equilibrium and mass transfer of  $Cu^{2+}$  towards the oil phase. Different anions formed different acids by means of cation exchange mechanism that determines the extent of cation exchange and hydrolysis reaction. The studied process also can be applied to other heavy metal ions with removal efficiency depending on the Lewis acidity of the corresponding metal ion.

#### Appendix A. Supplementary material

Supplementary data associated with this article can be found, in the online version, at <http://dx.doi.org/10.1016/j.seppur.2017.06.049>.

#### References

- [1] N.K. Shamas, L.K. Wang, *Water Supply and Distribution and Wastewater Removal*, third ed., John Wiley & Sons Inc, USA, 2011.
- [2] N.V. Paranychianakis, M. Salgot, S.A. Snyder, A.N. Angelakis, Water reuse in EU-states: necessity for uniform criteria to mitigate human and environmental risks, *Crit. Rev. Environ. Sci. Technol.* 45 (2015) 1409–1468.
- [3] M.A. Barakat, New trends in removing heavy metals from industrial wastewater, *Arab. J. Chem.* 4 (2011) 361–377.
- [4] A. Ihsanullah, A.M. Abbas, T. Al-Amer, M.J. Laoui, M.S. Al-Marri, M. Nasser, M.A. Khraisheh Atieh, Heavy metal removal from aqueous solution by advanced carbon nanotubes: critical review of adsorption applications, *Sep. Purif. Technol.* 157 (2016) 141–161.
- [5] M. Kul, K.O. Oskay, Separation and recovery of valuable metals from real mix electroplating wastewater by solvent extraction, *Hydrometallurgy* 155 (2015) 153–160.
- [6] M. Al-Shannag, Z. Al-Qodah, K. Bani-Melhem, M.R. Qtaishat, M. Alkasrawi, Heavy metal ions removal from metal plating wastewater using electrocoagulation: kinetic study and process performance, *Chem. Eng. J.* 260 (2015) 749–756.
- [7] J.-C. Lou, Y.-J. Huang, J.-Y. Han, Treatment of printed circuit board industrial wastewater by Ferrite process combined with Fenton method, *J. Hazard. Mater.* 170 (2009) 620–626.
- [8] A. Mahiroglu, E. Tarlan-Yel, M.F. Sevimli, Treatment of combined acid mine drainage (AMD)–flotation circuit effluents from copper mine via Fenton's process, *J. Hazard. Mater.* 166 (2009) 782–787.
- [9] A.S. Sheoran, V. Sheoran, Heavy metal removal mechanism of acid mine drainage in wetlands: a critical review, *Miner. Eng.* 19 (2006) 105–116.
- [10] J. LaDou, Printed circuit board industry, *Int. J. Hyg. Environ. Health* 209 (2006) 211–219.
- [11] M.K. Jha, D. Gupta, P.K. Choubey, V. Kumar, J. Jeong, J.-C. Lee, Solvent extraction of copper, zinc, cadmium and nickel from sulfate solution in mixer settler unit (MSU), *Sep. Purif. Technol.* 122 (2014) 119–127.
- [12] Y. Dong, J. Liu, M. Sui, Y. Qu, J.J. Ambuchi, H. Wang, Y. Feng, A combined microbial desalination cell and electro dialysis system for copper-containing wastewater treatment and high-salinity-water desalination, *J. Hazard. Mater.* 321 (2017) 307–315.
- [13] F. Fu, L. Xie, B. Tang, Q. Wang, S. Jiang, Application of a novel strategy—advanced Fenton-chemical precipitation to the treatment of strong stability chelated heavy metal containing wastewater, *Chem. Eng. J.* 189–190 (2012) 283–287.
- [14] L.K. Ong, P.L.T. Nguyen, F.E. Soetaredjo, S. Ismadji, Y.-H. Ju, Direct reuse of Cu-laden wastewater for non-edible oil hydrolysis: basic mechanism of metal extraction and fatty acid production, *RSC Adv.* 6 (2016) 25359–25367.
- [15] J.P. van der Hoek, H. de Fooij, A. Struiker, Wastewater as a resource: strategies to recover resources from Amsterdam's wastewater, *Resour. Conserv. Recy.* 113 (2016) 53–64.
- [16] S. Chang, J. Kamaruzaman, T. Tjoontow, I. Norli, Extraction of Cu(II) from aqueous solutions by vegetable oil-based organic solvents, in: 5th IASME/WSEAS International Conference on Energy & Environment World Scientific and Engineering Academy and Society (WSEAS), Wisconsin, USA, 2010, pp. 96–100.
- [17] A.D. Leonardi, V. Macciola, M.D. Felice, Copper and iron determination in edible vegetable oils by graphite furnace atomic absorption spectrometry after extraction with diluted nitric acid, *Int. J. Food Sci. Technol.* 35 (2000) 371–375.
- [18] T.A. Patil, D.N. Butala, T.S. Raghunathan, H.S. Shankar, Thermal hydrolysis of vegetable oils and fats. 1. Reaction kinetics, *Ind. Eng. Chem. Res.* 27 (1988) 727–735.
- [19] K. Larson, B. Raghuraman, J. Wienczek, Mass-transfer model of mercury removal from water via microemulsion liquid membranes, *Ind. Eng. Chem. Res.* 33 (1994) 1612–1619.
- [20] A.A. Alexandrov, K.A. Orlov, V.F. Ochkov, Thermophysical Properties of Thermal Power Engineering Working Substances, 2012. <<http://twm.mpei.ac.ru/rbtp/eng/>> (accessed 20.02.17).
- [21] S.I. Sandler, *Chemical, Biochemical, and Engineering Thermodynamics*, fourth ed., John Wiley & Sons, Inc., USA, 2006.
- [22] P.J. Sinko, Y. Singh, *Martin's Physical Pharmacy and Pharmaceutical Sciences: Physical, Chemical, and Biopharmaceutical Principles in the Pharmaceutical Sciences*, Lippincott Williams and Wilkins, USA, 2011.
- [23] D.C. Elliott, J.L. John Sealock, Aqueous catalyst systems for the water-gas shift reaction. 1. Comparative catalyst studies, *Ind. Eng. Chem. Prod. Res. Dev.* 22 (1983) 426–431.
- [24] J. Drzymala, Chemical equilibria in the oleic acid-water-NaCl system, *J. Colloid Interface Sci.* 108 (1985) 257–263.

- [25] L.K. Ong, P.L.T. Nguyen, F.E. Soetaredjo, S. Ismadji, Y.-H. Ju, Effect of subcritical water on homogeneous catalysis of used cooking oil hydrolysis, *RSC Adv.* 6 (2016) 64977–64985.
- [26] R. Alenezi, G.A. Leeke, R.C.D. Santos, A.R. Khan, Hydrolysis kinetics of sunflower oil under subcritical water conditions, *Chem. Eng. Res. Des.* 87 (2009) 867–873.
- [27] R.L. Holliday, J.W. King, G.R. List, Hydrolysis of vegetable oils in sub- and supercritical water, *Ind. Eng. Chem. Res.* 36 (1997) 932–935.
- [28] Y.-M. Lin, S.-C. Yen, Effects of additives and chelating agents on electroless copper plating, *Appl. Surf. Sci.* 178 (2001) 116–126.
- [29] E. Kir, Y. Çengelöglu, M. Ersöz, The effect of chelating agent on the separation of Fe(III) and Ti(IV) from binary mixture solution by cation-exchange membrane, *J. Colloid Interface Sci.* 292 (2005) 498–502.
- [30] S.A.A. Farha, N.A. Badawy, A.A. El-Bayaa, S.E. Garamon, The effect of chelating agent on the separation of some metal ions from binary mixture solution by cation-exchange resin, *Nat. Sci.* 8 (2010) 16–25.
- [31] C.-C. Wang, C.-H. Yang, C.-H. Lee, G.-H. Lee, Hydrothermal synthesis and structural characterization of a two-dimensional polymeric copper(II) complex containing an unusual bridged  $H_2edta^{2-}$  ligand, *Inorg. Chem.* 41 (2001) 429–432.
- [32] D. Mastropaolo, D.A. Powers, J.A. Potenza, H.J. Schugar, Crystal structure and magnetic properties of copper citrate dihydrate  $Cu_2C_6H_4O_7 \cdot 2H_2O$ , *Inorg. Chem.* 15 (1976) 1444–1449.
- [33] Y. Xue, S.J. Traina, Stability of metal-organic complexes in acetone- and methanol-water mixtures, *Environ. Sci. Technol.* 30 (1996) 3177–3183.
- [34] E. Yabalak, A.M. Gizir, Subcritical and supercritical fluid extraction of heavy metals from sand and sewage sludge, *J. Serb. Chem. Soc.* 78 (2013) 1013–1022.
- [35] W.A. Hermann, C.W. Kohlpaintner, Water-soluble ligands, metal complexes, and catalysts: synergism of homogeneous and heterogeneous catalysis, *Angew. Chem. Int. Ed.* 32 (1993) 1524–1544.
- [36] A.E. Martell, Critical stability constant, in: R.M. Smith (Ed.), Springer Science +Business Media, USA, 1989.
- [37] J.G. Neevel, Phytate: a potential conservation agent for the treatment of ink corrosion caused by iron galls, *Restaurator* 16 (1995) 143–160.
- [38] C.F. Baes, R.E. Mesmer, *The Hydrolysis of Cations*, John Wiley & Sons Inc, Canada, 1976.
- [39] A.E. Martell, Critical stability constant, in: R.M. Smith (Ed.), Springer Science +Business Media, USA, 1982.
- [40] J.R. Kanicky, D.O. Shah, Effect of premicellar aggregation on the pKa of fatty acid soap solutions, *Langmuir* 19 (2003) 2034–2038.
- [41] G. Akerlof, Dielectric constants of some organic solvent-water mixtures at various temperatures, *J. Am. Chem. Soc.* 54 (1932) 4125–4139.
- [42] J.C. Kotz, P.M. Treichel, J.R. Townsend, *Chemistry & Chemical Reactivity*, eighth ed., Brooks/Cole, USA, 2012.
- [43] NIST, NIST Chemistry WebBook, 2016. <<http://webbook.nist.gov/chemistry/>> (accessed 10.09.16).
- [44] J.M. Readnour, J.W. Cobble, Thermodynamic properties for the dissociation of bisulfate ion and the partial molal heat capacities of bisulfuric acid and sodium bisulfate over an extended temperature range, *Inorg. Chem.* 8 (1969) 2174–2182.
- [45] A.Y. Mulikidjanian, M.Y. Galperin, On the origin of life in the zinc world: 2. Validation of the hypothesis on the photosynthesizing zinc sulfide edifices as cradles of life on earth, in: H.H. Trimm (Ed.), *Inorganic Chemistry: Reactions, Structure and Mechanisms*, Apple Academic Press Inc., Canada, 2011, p. 125.