

78 Using the response surface methodology to establish the optimal conditions for preserving bananas by Shella Santoso

From Similarity check (check paper Jakad SPS)

Similarity Index	Similarity by Source	
8%	Internet Sources:	N/A
	Publications:	8%
	Student Papers:	N/A

Processed on 01-Mar-2022 11:40 WIB

ID: 1773585246

Word Count: 9441

sources:

- 1** 1% match (publications)
[Xin-Jie Loke, Chao-Kai Chang, Chih-Yao Hou, Kuan-Chen Cheng, Chang-Wei Hsieh. "Plasma-treated polyethylene coated with polysaccharide and protein containing cinnamaldehyde for active packaging films and applications on tilapia \(*Oreochromis niloticus*\) fillet preservation", *Food Control*, 2021](#)
- 2** 1% match (publications)
[Chun-Chi Hsieh, Chao-Kai Chang, Li-Wah Wong, Chung-Chi Hu, Jer-An Lin, Chang-Wei Hsieh. "Alternating current electric field inhibits browning of *Pleurotus ostreatus* via inactivation of oxidative enzymes during postharvest storage", *LWT*, 2020](#)
- 3** 1% match (publications)
[Lidia Ait Ouahioune, Magdalena Wrona, Cristina Nerín, Djamel Djenane. "Novel active biopackaging incorporated with macerate of carob \(*Ceratonia siliqua* L.\) to extend shelf-life of stored Atlantic salmon fillets \(*Salmo salar* L.\)", *LWT*, 2022](#)
- 4** 1% match (publications)
["Handbook of Electroporation", Springer Science and Business Media LLC, 2017](#)
- 5** 1% match (publications)
[Andi Syahrullah Sulaimana, Chao-Kai Chang, Chih-Yao Hou, Bara Yudhistira et al. "Effect of Oxidative Stress on Physicochemical Quality of Taiwanese Seagrape \(*Caulerpa lentillifera*\) with the Application of Alternating Current Electric Field \(ACEF\) during Post-Harvest Storage", *Processes*, 2021](#)
- 6** < 1% match (publications)
[J. Cao, S. Ma, L. Zhang, R. Wang, J. Shi. "Browning inhibition on fresh-cut potatoes by high voltage electrostatic field \(HVEF\) pre-treatment", *Acta Horticulturae*, 2021](#)
- 7** < 1% match (publications)
[Shella Permatasari Santoso, Artik Elisa Angkawijaya, Vania Bundjaja, Alfin Kurniawan et al. "Investigation of the influence of crosslinking activation methods on the physicochemical and Cu\(II\) adsorption characteristics of cellulose hydrogels", *Journal of Environmental Chemical Engineering*, 2022](#)
- 8** < 1% match (publications)
[M. T. Lafuente, L. Zacarias, M. A. Martínez-Téllez, M. T. Sanchez-Ballesta, E. Dupille. "Phenylalanine Ammonia-lyase As Related to Ethylene in the Development of Chilling Symptoms during Cold Storage of Citrus Fruits", *Journal of Agricultural and Food Chemistry*, 2001](#)

9 < 1% match (publications)

[C Chen. "Measurement of the efficiency of cell membrane electroporation using pulsed ac fields", Physics in Medicine and Biology, 09/07/2008](#)

10 < 1% match (publications)

[Rebecca M. Boys, Ngaio J. Beausoleil, Emma L. Betty, Karen A. Stockin. "When and how to say goodbye: An analysis of Standard Operating Procedures that guide end-of-life decision-making for stranded cetaceans in Australasia", Marine Policy, 2022](#)

11 < 1% match (publications)

[Li-Wah Wong, Xin-Jie Loke, Chao-Kai Chang, Wen-Ching Ko, Chih-Yao Hou, Chang-Wei Hsieh. "Use of the plasma-treated and chitosan/gallic acid-coated polyethylene film for the preservation of tilapia \(*Oreochromis niloticus*\) fillets", Food Chemistry, 2020](#)

12 < 1% match (publications)

[Zheng Zhang, Zhonghong Wu, Yuyao Yuan, Jiexian Zhang, Jia Wei, Bin Wu. "Sulfur dioxide mitigates oxidative damage by modulating hydrogen peroxide homeostasis in postharvest table grapes", Postharvest Biology and Technology, 2022](#)

13 < 1% match (publications)

[Samuel Herianto, Ming-Kuei Shih, Chia-Min Lin, Yu-Chi Hung et al. "The effects of glazing with plasma-activated water generated by a piezoelectric direct discharge plasma system on whiteleg shrimp \(*Litopenaeus vannamei*\)", LWT, 2022](#)

14 < 1% match (publications)

[His Lin, Ting-Yun Lin, Jer-An Lin, Kuan-Chen Cheng, Shella Permatasari Santoso, Chun-Hsu Chou, Chang-Wei Hsieh. "Effect of Pholiota nameko Polysaccharides Inhibiting Methylglyoxal-Induced Glycation Damage In Vitro", Antioxidants, 2021](#)

15 < 1% match (publications)

["Polymers for Agri-Food Applications", Springer Science and Business Media LLC, 2019](#)

16 < 1% match (publications)

[Huiyun Chen, Shuqian Zhou, Xia Li, Huqing Yang. "Exogenous progesterone alleviates chilling injury by upregulating lBAOX1 to mediate redox homeostasis and proline accumulation in postharvest sweetpotato tuberous root", Postharvest Biology and Technology, 2022](#)

17 < 1% match (publications)

[Sandra González-Casado, Olga Martín-Belloso, Pedro Elez-Martínez, Robert Soliva-Fortuny. "Enhancing the carotenoid content of tomato fruit with pulsed electric field treatments: Effects on respiratory activity and quality attributes", Postharvest Biology and Technology, 2018](#)

18 < 1% match (publications)

[Bin Wu, Qin Guo, Qingpeng Li, Yiming Ha, Xueping Li, Weixin Chen. "Impact of postharvest nitric oxide treatment on antioxidant enzymes and related genes in banana fruit in response to chilling tolerance", Postharvest Biology and Technology, 2014](#)

19 < 1% match (publications)

[Jeong-Seok Cho, Hyeon-Jeong Lee, Jung-Hoon Park, Jun-Hyung Sung, Ji-Young Choi, Kwang-Deog Moon. "Image analysis to evaluate the browning degree of banana \(*Musa spp.*\) peel", Food Chemistry, 2016](#)

paper text:

Food Packaging and Shelf Life 31 (2022) 100804 Contents lists available at ScienceDirect Food Packaging and Shelf Life journal homepage: www.elsevier.com/locate/fpsl Using the response surface methodology to establish the optimal conditions for preserving bananas (*Musa acuminata*) in a pulsed electric field and to decrease browning induced by storage at a low temperature Bo-Kuen Chen a, 1, Chao-Kai Chang a, 1, Kuan-Chen Cheng b, c, d, e, Chih-Yao Hou f, Jer-An Lin g, Min-Hung Chen h, Shella Permatasari Santoso i, j, Chang-Pen Chen k, Chang-Wei Hsieh a, d, * a Department of Food Science and Biotechnology, National Chung Hsing University, 145 Xingda Rd., South Dist., Taichung City 40227, Taiwan b Graduate

7Institute of Food Science and Technology, National Taiwan University, 1, Section 4, Roosevelt Road, Taipei 10617, Taiwan c Institute of Biotechnology, National Taiwan University, 1, Section 4, Roosevelt Road, Taipei 10617, Taiwan

d Department of Medical Research, China Medical University Hospital, Taichung City 404333, Taiwan e Department of Optometry, Asia University, 500, Lioufeng Rd., Wufeng, Taichung city 41354, Taiwan f Department of Seafood Science, National Kaohsiung University of Science and Technology, 142, Haizhuan Rd., Nanzi Dist., Kaohsiung City 81157, Taiwan g

14Graduate Institute of Food Safety, National Chung Hsing University, 145 Xingda Rd, South Dist, Taichung City 40227, Taiwan

h

13Agriculture and Food Agency (Marketing and Processing Division), Council of Agriculture, Executive Yuan, Nantou City, 54044, Taiwan i Department of

5Chemical Engineering, Widya Mandala Surabaya Catholic University, Kalijudan 37, Surabaya

, East Java 60114, Indonesia j

5Department of Chemical Engineering, National Taiwan University of Science and Technology, Keelung Rd. 43, Daan Dist, Taipei 10607, Taiwan

k Energy and Agile System Department, Metal Industries Research & Development Centre, 1001 Kaonan Highway, Kaohsiung City 821011, Taiwan ARTICLE INFO ABSTRACT Keywords: Pulsed electric field Response surface methodology Banana (*Musa acuminata*) Chilling injury Quality In this study, a

17pulsed electric field (PEF) was used to establish the preservation conditions of

bananas (*Musa* spp.) and explore the effect on chilling injury (CI) inhibition. The response surface methodology (RSM) demonstrated that the PEF strength of 50 kV m⁻¹ has a better inhibition effect on browning; however, adverse effects are caused when the PEF strength exceeds 100 kV m⁻¹ in comparison with untreated group. The optimal conditions established using RSM were PEF strength 32 kV m⁻¹, frequency 278 Hz, treatment time 32 min and width 600 μs, which can effectively inhibit the degree of banana browning by 131.6%. Further storage tests indicated that PEF could effectively improve fruit weight loss (18.91%), firmness (10.91%), browning and other changes associated with quality by maintaining the levels of total chlorophyll, carotenoids and ascorbic acid. This suggests that PEF has the potential to delay the CI of bananas stored at low temperatures and can maintain high fruit quality.

1. Introduction Banana (*Musa* spp.) is an economic crop that is widely planted in tropical and subtropical countries in Southeast Asia. Its crop yield is the fourth largest in the world, following that of rice, wheat and corn (Maduwanthi & Marapana, 2019). Similar to most tropical fruits, banana has a short storage period owing to its high respiration that limits its shelf life (Bhande, Ravindra, & Goswami, 2008). Although there are many preservation methods that inhibit respiration for preserving bananas, storage at a low temperature is still the most widely used method. However, the critical temperature for bananas is 13 °C, below which browning, corrosion and failure to mature will normally occur (Murmu & Mishra, 2018). Therefore, the shelf life of bananas is only approximately 3–7 days at room temperature (Chen et al., 2019). Chilling injury (CI) occurs when fruits and vegetables are harvested and stored at a specific low temperature (this temperature is also called *

11 Corresponding author at: Department of Food Science and Biotechnology, National Chung Hsing University, 145 Xingda Rd., South Dist., Taichung City 40227, Taiwan

E-mail addresses: sighr58796@gmail.com (B.-K. Chen), kai70219@nchu.edu.tw (C.-K. Chang), kccheng@ntu.edu.tw (K.-C. Cheng), chihyaohou@gmail.com (C.-Y. Hou), lja@nchu.edu.tw (J.-A. Lin), cmh@mail.afa.gov.tw (M.-H. Chen), shella@ukwms.ac.id (S.P. Santoso), cpchen@mail.mirdc.org.tw (C.-P. Chen), welson@nchu.edu.tw (C.-W. Hsieh).

11 These authors contributed equally to this study and share first authorship

3 <https://doi.org/10.1016/j.fpsl.2021>

100804 Received 3 July 2021; Received in revised form 15 December 2021; Accepted 25 December 2021 2214-2894/© 2021 Elsevier Ltd. All rights reserved. the critical temperature; tropical or subtropical fruits and vegetables have a higher critical temperature for cold damage, which can occur at 10–13 °C. However, the critical temperature for cold-tolerant fruits, such as lychees and pears, may be below 2 °C). When the fruit is stored in a cold-temperature environment, the cell membranes of fruits and vegetables are composed of fluids that turn into solid gels, which further causes the cells to fail to maintain their normal metabolic physiological functions (Zhang, Jiang, Cao, & Jiang, 2021). This further induces the accumulation of reactive oxygen species in the fruit and causes lipid oxidation of the cell membrane by phenylalanine ammonia-lyase. Simultaneously, the phenolic substances in the vacuole escape the cell and accelerate the action of polyphenol oxidase (PPO) in the cytoplasm to cause browning (Aghdam & Bodbodak, 2013; Nguyen et al., 2004). Methods of preventing CI

include the use of methyl jasmonate, methyl salicylate, 1-methylcyclopropene and other biological regulators (Rehman, Singh, & Khurshid, 2018) or the coating of the fruit/vegetable surface with edible films, such as wax (Murmu Mishra, 2018), which & have gradually become unacceptable to consumers. Although coating the fruit/vegetable surface using edible films reduces this doubt, the use of edible films still has disadvantages such as uneven coating uniformity and difficulty in batch quantification. Although physical methods, including hot water and steam treatment (Wang, Zhang, Xu, Huang, & Pang, 2012) as well as the use of modified atmosphere packaging (Nguyen, Ketsa, & van Doorn, 2004) are commonly used, heat treatment can cause the fruit to lose its natural texture or browning and modified atmosphere packaging is not necessarily suitable for the presentation of the fruit for sale (e.g., most bananas are sold without packaging). Therefore, the development of a fast, harmless physical method that can preserve nutrients is an urgent issue that needs to be addressed. A pulsed electric field (PEF) is an emerging non-thermal processing technology. Because the PEF has the characteristics of a square wave that are more likely to exhibit biological electromagnetic effects, PEFs have been used in the food industry for a variety of applications such as sterilisation, extraction, drying and frying (Arshad et al., 2020). PEFs are mostly applied for the preservation of agricultural products and food via sterilisation and drying (Mello, Fontana, Mulet, Corrêa, & Cárcel, 2021; Pallarés, Berrada, Tolosa, & Ferrer, 2021). However, deterioration in the quality (such as browning) that affects the storage period of agricultural products is mainly induced by respiration or enzyme action, and microbial contamination is not the most important factor that affects the purchase intention of consumers. Although PEF-assisted drying can inhibit the action of most of the enzymes, it cannot maintain the fresh flavour and appearance of agricultural products. However, related studies have shown that a PEF treatment of correct strength can enhance the antioxidant capacity of fruits and increase their phenolic compound content without destroying the tissue structure (Vallverdu-Queralt et al., 2012). These experiments confirmed that a PEF could induce reversible/ irreversible membrane perforation in plant cell membranes through a short-term high-energy impact. Such a membrane perforation phenomenon promotes the increase in plant secondary metabolites and thus enhances the ability of plants to resist adversity. In recent years, electric field (EF) treatment has been proven to delay post-harvest oxidative browning and tissue softening in crops, including oyster mushrooms (Hsieh et al., 2020) and persimmons (Liu et al., 2017), by regulating the activity of related enzymes. In addition, the EF treatment was proven to increase the antioxidant content of kidney beans and cabbage at low temperatures, improving their ability to resist storage at low temperatures (Cakmak, Dumlupinar, & Erdal, 2010). Based on the aforementioned literature, a PEF has the ability to inhibit the deterioration of agricultural products. It can simultaneously also protect agricultural products against stress by increasing secondary metabolite content. Therefore, PEF has the ability to inhibit the CI of bananas during storage at a low temperature. Related research has shown that EF parameters, such as the EF strength, frequency and processing time, have complex and interactive effects on plant cells (Gürsul, Gueven, Grohmann, & Knorr, 2016; Moharrami & Hashempour, 2021; Zhu, Wang, Vanga, & Raghavan, 2021). In recent years, researchers have gradually been able to simultaneously analyse the effect of variable factors, allowing the use of response surface methodology (RSM) in the optimal condition as an experimental design to examine the interactive influence of EF parameters on biological processing and the establishment of optimal conditions (Lal et al., 2021). Therefore, this study first used the RSM to explore the effect of PEF parameters on the inhibition of banana browning at low temperatures. A storage test was conducted to evaluate the effects of a PEF on the improvement in the quality of bananas stored at low temperature to study and establish PEF preservation modules for application to tropical fruits.

2. Materials and methods

2.1. Materials

The banana (*Musa acuminata* colla cv. Pei Chiao, AAA group) is a subspecies of Cavendish and is one of the main planted varieties in Taiwan. The bananas used in this study were purchased from Jiji Transportation and Marketing Cooperative (Nantou, Taiwan). The selection of bananas is based on the definition of commercial ripe bananas in related studies (Soltani, Alimardani, & Omid, 2011). The banana peel is turquoise instead of yellow, and those with no damage or disease in appearance are used as experimental samples.

2.2. Pulsed electric field treatment

and single-factor test The equipment used in this experiment is shown in Fig. 1. A laboratory-scale PEF device (PG403751, Youshang Technical Corp., Kaohsiung, Taiwan) with a DC supply (DSP-450-03-4HD, Chyng Hong Electronic CO., LTD, Taipei, Taiwan) was used to generate a maximum voltage of 40 kV, capacitance is 0.341 pF and current of 15 A. The generator provides a pulse width between 20 μ s and 1 s and a frequency of 1–1000 Hz. The processing chamber was combined with a refrigerator Fig. 1. Pulse electric field processing and storage device. and

4 consisted of parallel copper electrodes having a thickness of

1 mm, 0.1 M phosphate buffer, pH 6.8) at 4 °C for homogenisation and then length of 350 mm and width of 250 mm. The electrode spacing was fixed centrifuged at 4 °C, 15,000 \times g for 15 min. A spectrophotometer (CT- at 50 mm. Each banana finger weighed 160 \pm 5 g; three bananas were

28600, E-Chrom Tech Co. Ltd., Taiwan) was

used to measure the absor- packed in a plastic bag and placed on the lower electrode plate for the bance of the supernatant at 420 nm. The degree of browning was PEF treatment. expressed as OD420 100 g 1 fresh weight (Ali et al., 2021). – During processing, an oscilloscope (TBS1052C, Tektronix Inc., OR, USA) was used to monitor the stability of the output voltage, frequency 2.5. Chilling injury analysis and bandwidth of the PEF. The

8 temperature of the refrigerated room was maintained at 7 C 2 C during the

treatment process, and no signif- \pm 2.5.1. Appearance and CI index icant increase in the temperature of the processing space was found The degree of

18 the CI index was calculated using the following

for- during the storage process, which was monitored using an infrared non- mula provided in Eq. (3) (Nguyen et al., 2004): contact thermometer (TN498, Hila International Inc., Taipei, Taiwan). To establish the factor boundary of RSM, we first conducted a single- CI index = \sum CI scale \times fruit number at that scale factor analysis test of the inhibitory

17 effect of PEF on the degree of ba- Fruit number in

the group (3) nana browning. The single-factor analysis experimental design was The CI index is based on the degree of epidermal browning using a divided into four parts: (1) different PEF strengths of 25, 50, 75, 100, scale from 1 to 5, where 1 = no injury (no CI); 2 = mild injury (mild CI); 150, 200 and 250 kV m (Eq. (1)) (fixed width, frequency and treat- – 1 3 = moderate injury (moderate CI); 4 severe injury (severe CI); and 5 = ment time of 600 μ s, 50 Hz and 30 min, respectively); (2) different pulse = very severe CI (very severe CI). widths of 200, 400, 600, 800 and 1000 μ s (fixed strength, frequency and treatment time of 50 kV m– 1, 50 Hz and 30 min, respectively); (3) 2.5.2. Determination of fruit weight loss, total soluble solids and firmness different frequencies of 1, 50, 200, 350 and 500 Hz (fixed strength, The analysis of fruit weight loss was calculated from the change in width and treatment time of 50 kV m– 1, 600 μ s and 30 min, respec- the weight of the bananas during different storage periods using Eq. (4). tively); (4) different treatment times of

1, 15, 30, 45 and 60 min (fixed – (Elbagoury, Turoop, Runo, & Sila, 2021) strength, width and frequency of 50 kV m⁻¹, 600 μs and 50 Hz, respectively). The sample was maintained at 7 °C during processing (T1 – T2) Weight loss(%) = $\frac{T1 - T2}{T1} \times 100\%$ (4) cessing and storage, and after PEF treatment, to observe the change in T2 the degree of browning. where T1 is the fresh banana weight and T2 is the weight of bananas Electric field strength = kV in different treatment groups during different storage periods. m (1) The total soluble content (%) was measured using a refractometer (MASTER-53α, Atago Co., Ltd., Tokyo, Japan) after blending the pulp, where kV is the input voltage of the two electrode plates and m is the filtering the mixture and measuring the total soluble solid content of the distance between the two electrode plates. solution. The results were expressed as percentage. The firmness of the banana pieces was measured using a texture 2.3. Experimental design of response surface methodology analyser (Compac-100II, Sun Scientific Co., Ltd., Tokyo, Japan) according to related research with slight modification (Hao, Li, Xu, Huo, & RSM was used to optimise the PEF to the degree of browning of the Yang, 2019). The banana sample was cut in pieces to a size of 2 cm³ for banana peel. The model was constructed using Minitab version 16.0 analysis. The texture analyser was equipped with a cylindrical probe based on the results of the single-factor analysis when three independent with a 5-mm diameter, and Mode 1 was used. The ascending speed of the factors, namely, PEF strength (25–75 kV m⁻¹), frequency (50–500 Hz) stage for the test was 120.0 mm s⁻¹, and the maximum wave peak was and treatment time (10–60 min) were chosen, and the pulse width was the fruit firmness. The results were expressed as Newton (N) units. fixed at 600 μs. The method used had three levels as follows: three factors, Box Behnken and a central composite design consisting of 15 2.6. Determination of the quality index experimental runs, including three replications of a central point. The degree of browning was the dependent variable, which was expressed as Total chlorophyll and carotenoid content analyses were conducted a function of the independent variable using quadratic polynomial Eq. according to related research with slight modifications (Thakur et al., (2). The optimal conditions for the PEF for browning inhibition were 2019). Banana peel slices (1 g) were randomly selected from five sam- calculated as follows: ples. Pre-cooled 80% acetone (25 mL) was added to the samples, fol- $\sum_{i=1}^3 b_{ii}X_i^2 + \sum_{j=2}^3 \sum_{i=1}^3 b_{ij}X_iX_j$ (2) away from light. After filtering using a filter paper, a spectrophotometer $i = 1, i = 1j = i + 1$ was used to detect the absorbance at 663, 645 and 470 nm. The total chlorophyll content was expressed in mg 100 g⁻¹, whereas the total – where Y is the prediction of the degree of browning; b₀, b_i, b_{ii} and b_{ij} are carotene content was expressed in μg g⁻¹ and was calculated using the the model constant, linear regression coefficient, interact coefficient and following Eq. (5)–(8) (Wellburn, 1994): quadratic regression coefficient, respectively; and X_i and X_j are the Chlorophyll a(Ca) = $12.7 \times A_{663} - 2.995 \times A_{645}$ (5) coded values of independent variables. Chlorophyll b(Cb) = $22.95 \times A_{645} - 4.67 \times A_{663}$ (6) 2.4. Degree of browning Total chlorophyll mg100 (g- 1 (Ca + Cb) × V × 100) = (7) The peel (1 g) was mixed with 5 mL of 60% ethanol (dissolved in (W × 1000) Total carotenoid μgg⁻¹ () = $[1000 \times A_{470} - 3.27 \times Ca - 104 \times Cb]$ 198 (8) where A₄₇₀, A₆₄₅ and A₆₆₃ are the absorbance values at 470, 645 and 663 nm, respectively. W is the sample weight (g) and V is the volume of the solvent used (mL). The analysis of ascorbic acid in banana was performed using the 2,6-dichloroindophenol titration method (Hao et al., 2019). Separately, 10 g of the banana peel or pulp was weighed, mixed with 40 mL of 2% oxalic acid for homogenisation at 4 °C and then

16centrifuged at 12,000 g at 4 °C for 20 min. The supernatant (5 mL) was titrated with

0.25% 2,6-indo- phenol to a rose-red colour until the colour did not fade within 15 s. The 2,6-indophenol value was calibrated using ascorbic acid standards. The content of ascorbic acid in the fruit was expressed in mg 100 g⁻¹ FW. – 2.7. Statistical analysis RSM was conducted using SAS to conduct multiple regression anal- ysis and ANOVA analysis. SPSS Statistics 20.0 was used to conduct statistical data analysis. The experiments were conducted in five repli- cates, and the values were expressed as average and standard deviation. ANOVA was employed for significance analysis and Duncan’s multiple- range test for post hoc testing. A p value <0.05 indicated a significant difference (Granato, de Araújo Calado, & Jarvis, 2014).

23. Results and discussion 3.1. Effect of different parameters on the degree of browning of

banana Preliminary research indicates that PEF can reduce the PPO enzyme activity by altering the secondary and tertiary structures of this enzyme and that the inhibitory effect of the enzyme increases with the increase 2500 kV m⁻¹ and the treatment time was 124 μs, the enzyme activity in

4strength and treatment time. When the PEF strength is

increased to was the lowest (16.9%) (Zhong et al., 2007), indicating that PEF can delay the occurrence of enzymatic browning by reducing the PPO ac- tivity; moreover, it is speculated that it can further reduce the brown spots induced by CI. Some research has shown that irreversible/rever- sible electroporation increases the permeability of cell membranes and accelerates the release of polyphenols and the enzyme PPO to cause browning (Ade-Omowaye, Rastogi, Angersbach, & Knorr, 2003). In addition, it has been confirmed that when the PEF strength exceeds 120 kV m⁻¹, it causes irreversible electroporation of tomatoes, leading to cell apoptosis and acceleration of the deterioration of quality (Lafuente, Zacarias, Martínez-Téllez, Sanchez-Ballesta, & Granell,

4Fig. 2. Effect of different pulse electric field parameters on the degree of

browning of banana during cold storage: (A) strength (fixed width, frequency and treatment time of 600 μs, 50 Hz and 30 min, respectively), (B) treatment time (fixed strength, width and frequency of 50 kV m⁻¹, 600 μs and 50 Hz, respectively), (C) width (fixed strength, frequency and treatment time of 50 kV m⁻¹, 50 Hz and 30 min, respectively) and (D) frequency (fixed strength, width and treatment time of 50 kV m⁻¹, 600 μs and 30 min, respectively). a-d indicate significant differences between the values of each frequency at p < 0.05. 2003). Thus, optimising the parameter settings is essential. Fig. 2(A) presents the effect of different PEF strength (fixed width, frequency and treatment time of 600 μs, 50 Hz and 30 min, respectively) on

19the degree of browning of banana peel. The degree of

browning in the untreated group was 6.33 ± 0.12 (OD420 100 g⁻¹). After PEF treatments of 25, 50 and 75 kV m⁻¹, the increase in the degree of browning was – effectively delayed by 3.69 0.02, 2.79 0.03 and 4.67 0.02, of ± ± ± which the PEF treatment at 50 kV m⁻¹ was the most effective. However, – as the PEF

9strength was increased to 100 kV m⁻¹

, the degree of browning significantly increased by 9.78 ± 0.29; furthermore,

9when the PEF strength was increased to 250 kV m⁻¹

, the degree of browning continued to increase. This indicates that 100 kV m⁻¹ is the critical – 1 value for PEF treatment, above which the destruction of the cell mem- brane and the flow of intra-cellular material accelerates the browning of the peel. Fig. 2(B) presents the effect of different treatment times (fixed strength, width and frequency of 50 kV m⁻¹, 600 μs and 50 Hz, – respectively) on the degree of browning of the peel.

As the treatment time increased, the increase in the degree of browning reduced. When the treatment time reached 30 and 45 min, the lowest degree of browning was observed (3.56 ± 0.13 and 3.62 ± 0.05 , respectively), but when the treatment time reached 60 min, the degree of browning significantly increased

12 and was 1.4-fold higher than that of the control group

. Fig. 2(C) presents the effect of different pulse widths (fixed strength, frequency and treatment time of 50 kV m⁻¹, 50 Hz and 30 min, – respectively) on the

19 degree of browning. The degree of browning of the banana peel was

significantly reduced compared with the untreated group under different pulse width treatments. The treatments at 600 and 800 μ s resulted in the lowest degree of browning. The variations were 3.56 ± 0.01 and 3.34 ± 0.02 (OD₄₂₀ 100 g⁻¹), respectively, but no significant difference was observed. Previous studies showed that the pulse width may have a crucial relationship with the decline in enzyme activity (Ho, Mittal, & Cross, 1997). Previous studies also pointed out that regulating the pulse width of PEF between 2 and 8 μ s did not have a significant effect on the PPO enzyme activity (Marsellés-Fontanet & Mart ín-Belloso, 2007). However, in this study, using 200, 400 and 1000 μ s to inhibit browning was not as effective as using pulse widths of 600 and 800 μ s. This shows that the effect of pulse width on the inhibition of banana browning may not be linear; instead, a specific bandwidth has a more significant effect. Fig. 2(D) presents the effect of different frequencies (fixed strength, width and treatment time of 50 kV m⁻¹, 600 μ s and 30 min, respectively) on the degree of browning; the degree of browning decreases as the frequency increases. When the frequency was 350 Hz, the degree of browning of the fruit was as low as 2.93 ± 0.06 . However, when the frequency increased to 500 Hz, the degree of peel browning increased with no significant difference in comparison with the untreated group. A PEF strength of 25–75 kV m⁻¹, processing time of 10–60 min, frequency of 50–500 Hz and fixed pulse width of 600 μ s were subsequently chosen as the parameter ranges. Previous studies have shown that when the frequency was between 1–60 Hz and above 1000 Hz, the enzyme activity in pectin plums considerably decreased. The possible reason is that the activity endpoint of the enzyme is affected by the disturbance of the EF. However, it has also been shown that 100–1000 Hz promotes enzyme activity. The reason may be that the reaction rate between the enzyme and substrate is increased (Samaranayake & Sastry, 2016). This indicates that a PEF of 50 kV m⁻¹, 600 μ s and 350 Hz could effectively inhibit the PPO enzyme activity in bananas. However, when the PEF frequency reached 500 Hz, the browning reaction may be accelerated owing to the increase in the frequency of PPO contact with the substrate.

3.2. Response surface analysis Based on the experimental results, the function was obtained from Eq. (2) and Eq. (9). In the above four-factor single-factor analysis, a PEF strength (X1) of 25–75 kV/m, frequency (X2) of 50–500 Hz and processing time (X3) of 10–60 min were selected. The minimum degree of browning at #14 (50 kV m⁻¹, 275 Hz and 35 min) was 2.84 ± 0.01 , and the maximum at #12 (50 kV m⁻¹, 500 Hz and 60 min) was 9.85 ± 0.02 , – indicating that the minimum value was close to the centre point. In addition, the good coefficient of determination of the observed vs. predicted degree of browning values $R^2 = 0.9879$ suggested that the experiment was reliable (Supplement S1). $Y = 2.82 + 1.53625X_1 + 0.49625X_2 + 0.8425X_3 + 1.65625X_2^2 + 1.0025X_1X_2 + 0.4X_1X_3 + 2.06625X_2^2 + 0.525X_2X_3 + 2.65875X_2^3$ (9) Table 1 presents the variance analysis of the surface regression. The p value of the total model was 0.0003, indicating that the model is significant ($p < 0.05$). The suitability of the model was tested using the < lack-of-fit test. The p value of the lack-of-fit test was 0.0858, which did not reach a level of significance ($p > 0.05$), suggesting that the experimental data fit the model. Similarly, the linear factors X1 (strength), X2 (frequency) and X3 (time) had significant effects on the degree of browning ($p < 0.05$) (Table 1). In the quadratic factor form, X1² (strength), X2² (frequency) and X3² (time) had significant effects on the degree of browning ($p < 0.05$). From the interaction factor, only X1 X2 (strength frequency) × × had a significant effect on the degree of browning ($p < 0.05$), whereas < the remaining factors X1 × X3 (strength ×

time) and $X_2 \times X_3$ (frequency \times time) were not significant ($p > 0.05$). Fig. 3(A) presents the results at a fixed frequency of 275 Hz. The effect of the PEF strength and treatment time on the degree of browning has been discussed. When the PEF strength was 40–50 kV m^{-1} and the treatment time was 25–35 min, the lowest browning variability was observed. Fig. 3(B) presents the results at a fixed treatment time of 35 min. The effect of the PEF strength and frequency on the degree of browning is discussed. When the PEF strength was 40–50 kV m^{-1} and the frequency was 200–300 Hz, the browning variability was the lowest. Fig. 3(C) presents the results at a fixed PEF strength of 50

9 kV m^{-1} . The effect of the treatment time and frequency on the degree of

browning is discussed. When the frequency was 250–300 Hz and the treatment time was 30–35 min, the lowest degree of browning was observed. The literature shows that the closer the contours are to the ellipse, the stronger is the interaction between the two variables. In contrast, the closer the contours are to the circle, the weaker is the interaction between the two variables (Wang et al., 2020). It can be observed from Fig. 3 that when the treatment time is fixed, the contour graph of strength and time is close to ellipse, indicating that the mutual influence is higher. These results are in accordance with those presented in Table 1. Table 1 Analysis of variance for the regression model. Source DF Sum of squares F Value Prob>Fa Model 9 74.28 X_1 1 18.88 X_2 1 1.97 X_3 1 5.67 X_{12} 1 9.00 X_{22} 1 14.35 X_{32} 1 24.27 $X_1 \times X_2$ 1 4.02 $X_1 \times X_3$ 1 0.64 $X_2 \times X_3$ 1 1.10 Lack of fit 3 0.83 Pure Error 2 0.05 Total Error 5 0.89 * significant difference ($p < 0.05$) 46.57 106.39 11.10 31.99 50.72 80.85 136.76 22.65 3.61 6.21 10.81 0.0003* 0.0001* 0.0207* 0.0024* 0.0008* 0.0003* <0.0001* 0.0051* 0.1160 0.0550 0.0858 Fig. 3. The surface plots show the effects of different variables on the degree of browning at (A) a fixed treatment time at the zero level of 35 min, (B) fixed frequency at the zero level of 275 Hz and (C) fixed strength at the zero level of 50 kV m^{-1} . The results of the ridge analysis showed that the PEF strength of 37.93 kV m^{-1} , frequency of 278.18 Hz and treatment time of 31.79 min – may have the best effect on inhibiting the browning of banana when stored at 7 °C. The ridge analysis results also show that increasing the PEF strength to 40.44 kV m^{-1} , frequency to 285.42 Hz or extending the PEF treatment time has no significant effect on inhibiting banana browning. Therefore, considering future industrial practical applications, we use the following parameters: a PEF strength of 38 kV m^{-1} ,

4 frequency of 278 Hz, pulse width of 600 μs and processing time of

32 min to carry out a PEF experiment to delay the CI of bananas under low temperature storage 3.3. Change in appearance and CI during cold storage When bananas are stored below 13 °C, CI is mainly characterised by the browning of the peel, which is accompanied by large areas of brown spots.

18 Fig. 4(A) shows the effect of

untreated and PEF treatments on banana appearance

15 during cold storage at 7 °C for 20 days. In the

untreated sample, brown spots started to show on the 5th day;

4 in the PEF- treated sample, they did not appear

until the 10th day. The degree of brown spots on the 20th day

4 in the PEF-treated sample was similar to that in the

untreated sample on the 15th day. In addition, the appearance of black spots on the 20th day in the PEF-treated sample was not as severe as that in the untreated group. This shows that PEF could effectively improve the deterioration of appearance in banana CI. Fig. 4(B) presents the change in the CI index at 7 °C for 20 days (level 0, no CI; level 1–2, slight; level 3, moderate; level 4, severe, with a browning area of >75%). Fresh bananas showed no symptoms of CI; all samples showed CI symptoms after 5 days of storage that increased with storage time; however, in the storage conditions of 7 °C and 20 days, the CI index

6 in the PEF-treated group was lower than in the untreated group. In the

first 10

8 days of the storage period, the CI index of the PEF-treated

group was only approximately 40%–70% of that of the untreated group; during days 10–20, the

8 CI index of the PEF-treated group was 70%–85% of that of the

untreated group. Previous studies have demonstrated that the EF effect can inhibit the activity of lipoxygenase and PPO in oyster mushrooms to maintain high cell membrane integrity and delay the browning of oyster mushrooms during storage (Hsieh et al., 2020). Previous studies have shown that using 100 kV m⁻¹ and 50 Hz PEF – to treat *Phaseolus vulgaris* and *Brassica oleracea* for 10 min could effectively increase the superoxide dismutase activity of *P. vulgaris* and *B. oleracea* and reduce H₂O₂ production (Cakmak et al., 2010). In this study, the use of PEF at 38 kV m⁻¹ and 278 Hz could also effectively – 1 suppress the CI value of bananas. Therefore, PEF may improve the Fig. 4. Effect of the pulse electric field treatment on the (A) appearance and (B) chilling injury index in bananas during cold storage at 7 °C for 20 days. * The CI index was

1 significantly different on the same day ($p < 0.05$

).

4 Table 2 Effect of PEF treatment on

quality changes in bananas during cold storage at 7 °C for 20 days. Storage time Day0 Day5 Day10 Day15 Day20 Weight loss (%) Untreated - 0.47 ± 0.06 Da 1.10 ± 0.07Ca 1.69 ± 0.27Ba 2.36 ± 0.22Aa PEF treated - 0.40 ± 0.05 Da 0.79 ± 0.13Cb 1.21 ± 0.07Bb 1.91 ± 0.18Ab Toughness (N) Untreated 19.69 ± 0.34Ca 19.28 ± 0.64Ca 23.81 ± 0.47Aa 22.14 ± 0.57Ba 19.24 ± 0.35Ca PEF treated 19.69 ± 0.34Ba 18.45 ± 0.43Cb 20.75 ± 0.49Ab 19.57 ± 0.43Bb 17.13 ± 0.30Db TSS (%) Untreated 17.26 ± 0.51Da 20.20 ± 0.36Cb 21.60 ± 0.13Bb 21.84 ± 0.23Bb 22.30 ± 0.39Aa PEF treated 17.26 ± 0.51Ca 20.98 ± 0.37Ba 22.32 ± 0.27Aa 22.64 ±

0.23Aa 22.54 ± 0.26Aa Chlorophyll Untreated 9.16 ± 0.66Aa 2.80 ± 0.13Ba 2.04 ± 0.04Cb 1.82 ± 0.03CDb
 1.46 ± 0.06Db (mg 100 g⁻¹) PEF treated 9.16 ± 0.66Aa 2.86 ± 0.27Ba 2.38 ± 0.06Ca 2.36 ± 0.22BCa 2.37
 ± 0.07BCa Carotenoid Untreated 0.52 ± 0.02Ea 1.06 ± 0.01Ab 0.91 ± 0.01Bb 0.88 ± 0.01Cb 0.79 ± 0.03Db
 (µg g⁻¹) PEF treated 0.52 ± 0.02Da 1.35 ± 0.01Aa 1.02 ± 0.01Ca 1.07 ± 0.01Ba 1.01 ± 0.01Ca Ascorbic
 acid Peel Untreated 4.44 ± 0.28Aa 3.19 ± 0.06Bb 2.81 ± 0.08Cb 2.55 ± 0.11Db 1.85 ± 0.09Eb (mg 100 g⁻¹)
 PEF treated 4.44 ± 0.28Aa 3.55 ± 0.20Ca 3.84 ± 0.07Ba 2.74 ± 0.09Da 2.40 ± 0.21Ea Pulp Untreated 6.48 ±
 0.22Aa 6.15 ± 0.26Bb 4.65 ± 0.15Cb 4.27 ± 0.28Db 4.04 ± 0.12Ea PEF treated 6.48 ± 0.22Ba 7.00 ± 0.14Aa
 5.13 ± 0.08Ca 4.63 ± 0.09Da 3.88 ± 0.14Ea Values are expressed as mean ± standard deviation. a-b

2Means followed by different superscripts in the same row are significantly different at

the same storage time (

2p < 0.05). A-E Means followed by different superscripts in the same column are significantly different at the same treatment. (p < 0.05

) antioxidant capacity of bananas against cold-induced browning by altered enzyme activity. 3.4. Change in the weight loss, total soluble solids and firmness during cold storage Water loss is a phenomenon of CI. Cell membrane damage causes water and weight loss of the fruit (Wang et al., 2019). As shown in Table 2, in the first 5 days of storage, no significant difference was observed in the weight loss rate between the two groups, but the PEF-treated group showed a significantly delayed increase in the weight loss rate after the 10th day. The weight loss rate was delayed by 28.30% and 18.91% on the 15th and 20th days, respectively. Previous studies using ultrasound combined with salicylic acid showed effective reduction in the weight loss of bananas during storage at a low temperature by approximately 55% (Khademi, Ashtari, & Razavi, 2019). In addition, applying a combination of methyl salicylate and calcium chloride to bananas reduced the weight loss rate of bananas during storage at low temperature by 30% (Elbagoury et al., 2021). These studies also show that the weight loss rate of bananas during storage is positively correlated with the integrity of the fruit cell membrane. At the same time, reducing cell membrane damage can also reduce oxidative damage and improve fruit browning. Abnormal ripening is also one of the signs of CI to bananas, which causes the fruit that may fail to soften. Studies have demonstrated that at storage at a low temperature, the low activity of starch-related degrading enzymes results in high firmness and low TTS content, leading to the firmness of bananas (Song et al., 2019). The results indicated that the toughness of the peel increased during storage and the toughness of the peel value was reach a maximum on the 10th day, followed by a decrease; similar phenomena were observed in previous studies (Wang et al., 2013). The firmness

6in the PEF-treated group was significantly lower than that in the untreated group during storage. On the 20th day of storage, the firmness of the PEF-treated and

untreated groups was 17.13 ± 0.30 and 19.24 ± 0.35 N, respectively, and it decreased by approximately 10.97% in the PEF-treated group, indicating that PEF treatment can maintain the toughness of banana peels. The same results can be observed in the content of soluble solids. Under normal ripening conditions, the starch in the fruit will be hydrolysed into soluble sugars, such as glucose, fructose and sucrose, thereby increasing the content of soluble solids. Conversely, under storage at a low temperature, the increase in the content of soluble solids is delayed (Chen, Zhao, Wu, He, & Yang, 2020). 3.5. Changes in the levels of chlorophyll, carotenoid and ascorbic acid during cold storage The chlorophyll content of bananas is

degraded during the ripening period, and the carotenoid content increases (Pongprasert, Sekozawa, Sugaya, & Gemma, 2011). Storage at low temperatures will cause damage to the chlorophyll thylakoid membrane, resulting in substantial degradation of chlorophyll and production of excessive free radicals that accelerate the CI of the fruit. Table 2 points out that PEF treatment does not cause adverse effects on chlorophyll. Although both PEF-treated and untreated banana chlorophyll will decrease with the storage time, the PEF-treated group maintained the same chlorophyll level at $2.37 \pm 0.07 \text{ mg } 100 \text{ g}^{-1}$ whereas the chlorophyll content of the untreated group continued to drop to $1.46 \pm 0.06 \text{ mg } 100 \text{ g}^{-1}$ in the middle and late stages of storage. Previous studies have pointed out that the glycine betaine in chlorophyll can resist the oxidative damage caused by CI (Aghdam & Bododak, 2013; Nguyen et al., 2004). The additional addition of glycine betaine with antioxidant capacity can also greatly reduce the structural damage caused by CI to cell membranes. (Rodríguez-Zapata et al., 2015). Therefore, Table 2 also shows that the PEF may reduce the structural damage caused by CI and simultaneously reduce the loss of banana chlorophyll when stored at 7°C , thereby reducing the phenomenon of banana epidermal browning. Carotenoids are secondary metabolites of plants that scavenge free radicals to resist a harsh external environment and maintain normal $0.52 \text{ to } 1.06 \text{ } \mu\text{g } 100 \text{ g}^{-1}$ (untreated I group) and 1.35 metabolism (Krinsky, 1998). Table 2 shows the values increasing from $\pm \pm \pm 0.01 \text{ } \mu\text{g } 100 \text{ g}^{-1}$ (PEF-treated group) in the 5 days before storage and decreased to 1.46 ± 0.06 and $1.01 \pm 0.01 \text{ } \mu\text{g } 100 \text{ g}^{-1}$, respectively, during storage; similar phenomena have also been found in previous study (Rodríguez-Zapata et al., 2015). According to the above-mentioned findings, the carotenoid content

12 in the PEF-treated group during storage was higher than that in the untreated group

, suggesting that PEF treatment alleviates the symptoms of CI by increasing the carotenoid content. Previous studies have demonstrated that processing tomato fruits for 30 pulses at 200 kV m^{-1} and storing them at 4°C for $\approx 24 \text{ h}$ can effectively increase the total carotenoid content by approximately 30% (González-Casado, Martín-Belloso, Elez-Martínez, & Soliva-Fortuny, 2018).

2 In this study, the total carotenoid content increased by approximately

21%

2 compared with the untreated group on the 5th day of storage

. Ascorbic acid is a non-enzymatic water-soluble antioxidant that can effectively remove free radicals in fruits. Numerous studies have pointed out that maintaining the ascorbic acid content during storage at low temperature can effectively delay the occurrence of CI (Liu, Li, Liang, Jiang, & Chen, 2019). As shown in Table 2, the ascorbic acid content in treated group decreased from $4.44 \text{ to } 1.85 \text{ } \text{mg } 100 \text{ g}^{-1}$ the peel after storage decreases. The ascorbic acid content in the un- $\pm \pm$, whereas the ascorbic acid content in the PEF-treated group decreased from 4.44 ± 0.28 to $2.40 \pm 0.21 \text{ mg } 100 \text{ g}^{-1}$. This result showed that after the PEF treatment of bananas, a higher ascorbic acid content remains in the banana during the storage period than untreated bananas. Simultaneously, the ascorbic acid content in the pulp also decreased with the increase in the storage time and the ascorbic acid content in the PEF group increased over the first 5 days, from $6.48 \text{ to } 7.00 \text{ } \text{mg } 100 \text{ g}^{-1}$, and then decreased. Overall, the ascorbic acid content of the PEF treatment group was significantly higher than that of the untreated group 15 days before storage. However, no difference was observed between the two groups after the 20th day and similar phenomena have also been found in previous studies (Hao et al., 2019), where bananas treated with exogenous progesterone showed a delay in the degradation of ascorbic acid during storage and enhancement of their

antioxidant capacity to resist CI. electrostatic field of 0.02 kV cm⁻¹ for 2 h increased the ascorbic acid A related study pointed out that treatment with a high-voltage content of tomatoes (Zhao, Hao, Xue, Liu, Li, 2011). Another study & indicated that treatment at 430 kV m⁻¹ for 2 h did not increase the ascorbic acid content of tomatoes (Bajgai, Hashinaga, Isobe, Vijaya Raghavan, Ngadi, 2006). In this study, a PEF strength of 38 kV m & - 1 was used and treatment for 32 min was shown to increase the ascorbic acid content of bananas. This also showed that appropriate EF treatment was helpful in improving the antioxidant ability of fresh fruit during a period of storage at low temperature after harvest, thereby improving the reduction in browning caused by CI or oxidative damage. 4. Conclusion In this study, the PEF process (a PEF strength of 38 kV m⁻¹, frequency of 278 Hz, treatment time of 32 min and pulse width of 600 μs) established by RSM can effectively reduce the CI of bananas, thereby reducing the browning phenomenon (15 to 50%) caused by bananas when stored at low temperatures. Furthermore, the results of the quality change test showed that the PEF treatment group could avoid the decline in firmness and weight loss of bananas during storage at 7 C and effectively maintain the carotenoids, chlorophyll and ascorbic acid content. Such results indicate that PEF treatment not only improves the resistance of tropical fruits to low temperature and CI but also does not adversely affect the nutrient content of the fruit or related post-ripening indicators. It also means that the application of PEF in food and agri- culture should not only be limited to sterilisation and auxiliary extrac- tion/drying but also can be used in the post-harvest treatment of fruits and vegetables in the future to prolong the quality of produce during the period in which they are sold.

1CRediT authorship contribution statement Bo-Kuen Chen: **Conceptualization, Methodology, Software, Data curation, Writing – original draft, Visualization, Investigation, Chao-Kai Chang: Conceptualization, Methodology, Software, Data curation, Writing – original draft, Visualization, Investigation**

, Software, Validation, Writing – review & editing, Kuan-Chen Cheng: Data curation,

1Writing – original draft, Visualization, Investigation, Software, Validation, Writing – review & editing, Chih-Yao Hou: Visualization, Investigation, **Software, Validation, Writing – review & editing**

, Jer-An Lin:

1Software, Validation, Writing – review & editing, Min-Hung **Chen**: Visualization, Investigation, **Supervision**

, Shella Permatasari Santoso: Visualization, Investigation, Software, Validation, Chang-Pen Chen: Visualization, Investigation, Supervision,

1Writing – review & editing, Chang-Wei Hsieh: Conceptualization, Methodology, Software, Data curation, Writing – original draft, Supervision, Writing – review & editing

1 Acknowledgements The authors wish to thank the Ministry of Science and Technology, Taiwan (grant no. 110-2221-E-005-012-MY3

, 110-2811-E-005-514) and NCHU-MIRDC Bilateral Joint Research Project

5for their financial support. **Conflicts of interest** The authors declare no conflict of interest

10 Appendix A. Supporting information Supplementary data associated with this article can be found in the online version at doi:10.1016/j.fpsl.2021

.100804. References Ade-Omowaye, B., Rastogi, N., Angersbach, A., & Knorr, D. (2003). Combined effects of pulsed electric field pre-treatment and partial osmotic dehydration on air drying behaviour of red bell pepper. *Journal of Food Engineering*, 60(1), 89–98. [https://doi.org/10.1016/S0260-8774\(03\)00021-9](https://doi.org/10.1016/S0260-8774(03)00021-9)

Aghdam, M. S., & Bodbodak, S. (2013). Physiological and biochemical mechanisms regulating chilling tolerance in fruits and vegetables under postharvest salicylates and jasmonates treatments. *Scientia Horticulturae*, 156, 73–85. <https://doi.org/10.1016/j.scienta.2013.03.028>

Ali, S., Sattar Khan, A., Ullah Malik, A., Anwar, R., Akbar Anjum, M., Nawaz, A., ... Naz, S. (2021). Combined application of ascorbic and oxalic acids delays postharvest browning of litchi fruits under controlled atmosphere conditions. *Food Chemistry*, 350, Article 129277. <https://doi.org/10.1016/j.foodchem.2021.129277>

Arshad, R. N., Abdul-Malek, Z., Munir, A., Buntat, Z., Ahmad, M. H., Jusoh, Y. M. M., ... Aadil, R. M. (2020). Electrical systems for pulsed electric field applications in the food industry: An engineering perspective. *Trends in Food Science & Technology*, 104, 1–13. <https://doi.org/10.1016/j.tifs.2020.07.008>

Bajgai, T. R., Hashinaga, F., Isobe, S., Vijaya Raghavan, G. S., & Ngadi, M. O. (2006). Application of high electric field (HEF) on the shelf-life extension of emblic fruit (*Phyllanthus emblica* L.). *Journal of Food Engineering*, 74(3), 308–313. <https://doi.org/10.1016/j.jfoodeng.2005.03.023>

Bhande, S. D., Ravindra, M. R., & Goswami, T. K. (2008). Respiration rate of banana fruit under aerobic conditions at different storage temperatures. *Journal of Food Engineering*, 87(1), 116–123. <https://doi.org/10.1016/j.jfoodeng.2007.11.019>

Cakmak, T., Dumlupinar, R., & Erdal, S. (2010). Chilling resistance of *Phaseolus vulgaris* and *Brassica oleracea* under a high-intensity electric field. *Zeitschrift Für Naturforschung C*, 65(5–6), 380–386. <https://doi.org/10.1515/znc-2010-5-610>

Chen, J., Li, F., Li, Y., Wang, Y., Wang, C., Yuan, D., & Jiang, Y. (2019). Exogenous procyanidin treatment delays senescence of harvested banana fruit by enhancing antioxidant responses and in vivo procyanidin content. *Postharvest Biology and Technology*, 158, Article 110999. <https://doi.org/10.1016/j.postharvbio.2019.110999>

Chen, L., Zhao, X., Wu, J. e, He, Y., & Yang, H. (2020). Metabolic analysis of salicylic acid-induced chilling tolerance of banana using NMR. *Food Research International*, 128, Article 108796. <https://doi.org/10.1016/j.foodres.2019.108796>

Elbagoury, M. M., Turoop, L., Runo, S., & Sila, D. N. (2021). Regulatory influences of methyl jasmonate and calcium chloride on chilling injury of banana fruit during cold storage and ripening. *Food Science & Nutrition*, 9(2), 929–942. <https://doi.org/10.1002/fsn3.2058>

Gürsul, I., Gueven, A., Grohmann, A., & Knorr, D. (2016). Pulsed electric fields on phenylalanine ammonia lyase activity of tomato cell culture. *Journal of Food Engineering*, 188, 66–76. <https://doi.org/10.1016/j.jfoodeng.2016.05.007>

González-Casado, S., Martín-Belloso, O., Elez-Martínez, P., & Soliva-Fortuny, R. (2018). Enhancing the carotenoid content of tomato fruit with pulsed electric field treatments: Effects on respiratory activity and quality attributes. *Postharvest Biology and Technology*, 137, 113–118. <https://doi.org/10.1016/j.postharvbio.2017.11.017>

Granato, D., de Araújo Calado, V. M., & Jarvis, B. (2014). Observations on the use of statistical methods in food science and technology. *Food Research*

International, 55, 137–149. <https://doi.org/10.1016/j.foodres.2013.10.024> Hao, J., Li, X., Xu, G., Huo, Y., & Yang, H. (2019). Exogenous progesterone treatment alleviates chilling injury in postharvest banana fruit associated with induction of alternative oxidase and antioxidant defense. *Food Chemistry*, 286, 329–337. <https://doi.org/10.1016/j.foodchem.2019.02.027> Ho, S. Y., Mittal, G. S., & Cross, J. D. (1997). Effects of high field electric pulses on the activity of selected enzymes. *Journal of Food Engineering*, 31(1), 69–84. [https://doi.org/10.1016/S0260-8774\(96\)00052-0](https://doi.org/10.1016/S0260-8774(96)00052-0) Hsieh, C.-C., Chang, C.-K., Wong, L.-W., Hu, C.-C., Lin, J.-A., & Hsieh, C.-W. (2020). Alternating current electric field inhibits browning of *Pleurotus ostreatus* via inactivation of oxidative enzymes during postharvest storage. *LWT*, 134, Article 110212. <https://doi.org/10.1016/j.lwt.2020.110212> Khademi, O., Ashtari, M., & Razavi, F. (2019). Effects of salicylic acid and ultrasound treatments on chilling injury control and quality preservation in banana fruit during cold storage. *Scientia Horticulturae*, 249, 334–339. <https://doi.org/10.1016/j.scienta.2019.02.018> Krinsky, N. I. (1998). The antioxidant and biological properties of the carotenoids. *Annals of the New York Academy of Sciences*, 854(1), 443–447. <https://doi.org/10.1111/j.1749-6632.1998.tb09923.x> Lafuente, M. T., Zacarias, L., Martínez-Téllez, M. A., Sanchez-Ballesta, M. T., & Granel, A. (2003). Phenylalanine ammonia-lyase and ethylene in relation to chilling injury as affected by fruit age in citrus. *Postharvest Biology and Technology*, 29(3), 309–318. [https://doi.org/10.1016/S0925-5214\(03\)00047-4](https://doi.org/10.1016/S0925-5214(03)00047-4) Lal, A. M. N., Prince, M. V., Kothakota, A., Pandiselvam, R., Thirumdas, R., Mahanti, N. K., & Sreeja, R. (2021). Pulsed electric field combined with microwave-assisted extraction of pectin polysaccharide from jackfruit waste. *Innovative Food Science & Emerging Technologies*, 74, Article 102844. <https://doi.org/10.1016/j.ifset.2021.102844> Liu, C.-E., Chen, W.-J., Chang, C.-K., Li, P.-H., Lu, P.-L., & Hsieh, C.-W. (2017). Effect of a high voltage electrostatic field (HVEF) on the shelf life of persimmons (*Diospyros kaki*). *LWT*, 75, 236–242. <https://doi.org/10.1016/j.lwt.2016.08.060> Liu, J., Li, F., Liang, L., Jiang, Y., & Chen, J. (2019). Fibroin delays chilling injury of postharvest banana fruit via enhanced antioxidant capability during cold storage. *Metabolites*, 9(7), 152. <https://doi.org/10.3390/metabo9070152> Maduwanthi, S. D. T., & Marapana, R. A. U. J. (2019). Induced ripening agents and their effect on fruit quality of banana. *International Journal of Food Science*, 2019. <https://doi.org/10.1155/2019/2520179> Marsellés-Fontanet, Á. R., & Martín-Belloso, O. (2007). Optimization and validation of PEF processing conditions to inactivate oxidative enzymes of grape juice. *Journal of Food Engineering*, 83(3), 452–462. <https://doi.org/10.1016/j.jfoodeng.2007.04.001> Mello, R. E., Fontana, A., Mulet, A., Corrêa, J. L. G., & Cárcel, J. A. (2021). PEF as pretreatment to ultrasound-assisted convective drying: Influence on quality parameters of orange peel. *Innovative Food Science & Emerging Technologies*, 72, Article 102753. <https://doi.org/10.1016/j.ifset.2021.102753> Moharrami, S., & Hashempour, H. (2021). Comparative study of low-voltage electric field-induced, ultrasound-assisted and maceration extraction of phenolic acids. *Journal of Pharmaceutical and Biomedical Analysis*, 202, Article 114149. <https://doi.org/10.1016/j.jpba.2021.114149> Murmu, S. B., & Mishra, H. N. (2018). Post-harvest shelf-life of banana and guava: Mechanisms of common degradation problems and emerging counteracting strategies. *Innovative Food Science & Emerging Technologies*, 49, 20–30. Nguyen, T. B. T., Ketsa, S., & van Doorn, W. G. (2004). Effect of modified atmosphere packaging on chilling-induced peel browning in banana. *Postharvest Biology and Technology*, 31(3), 313–317. <https://doi.org/10.1016/j.postharvbio.2003.09.006> Pallarés, N., Berrada, H., Tolosa, J., & Ferrer, E. (2021). Effect of high hydrostatic pressure (HPP) and pulsed electric field (PEF) technologies on reduction of aflatoxins in fruit juices. *LWT*, 142, Article 111000. <https://doi.org/10.1016/j.lwt.2021.111000> Pongprasert, N., Sekozawa, Y., Sugaya, S., & Gemma, H. (2011). A novel postharvest UV-C treatment to reduce chilling injury (membrane damage, browning and chlorophyll degradation) in banana peel. *Scientia Horticulturae*, 130(1), 73–77. <https://doi.org/10.1016/j.scienta.2011.06.006> Rehman, M., Singh, Z., & Khurshid, T. (2018). Methyl jasmonate alleviates chilling injury and regulates fruit quality in 'Midknight' Valencia orange. *Postharvest Biology and Technology*, 141, 58–62. <https://doi.org/10.1016/j.postharvbio.2018.03.006> Rodríguez-Zapata, L. C., Espadas y Gil, F. L., Cruz-Martínez, S., Talavera-May, C. R., Contreras-Marin, F., Fuentes, G., ... Santamaría, J. M. (2015). Preharvest foliar applications of glycine-betaine protects banana fruits from chilling injury during the postharvest stage. *Chemical and Biological Technologies in Agriculture*, 2(1), 1–10. <https://doi.org/10.1186/s40538-015-0032-6> Samaranayake, C. P., & Sastry, S. K. (2016). Effects of controlled-frequency moderate electric fields on pectin methylesterase and polygalacturonase activities in tomato homogenate. *Food Chemistry*, 199, 265–

272. <https://doi.org/10.1016/j.foodchem.2015.12.010> Soltani, M., Alimardani, R., & Omid, M. (2011). Evaluating banana ripening status from measuring dielectric properties. *Journal of Food Engineering*, 105(4), 625–631. <https://doi.org/10.1016/j.jfoodeng.2011.03.032> Song, Z., Qin, J., Zheng, Q., Ding, X., Chen, W., Lu, W., ... Zhu, X. (2019). The involvement of the banana f-box protein maebf1 in regulating chilling-inhibited starch degradation through interaction with a MaNAC67-like protein. *Biomolecules*, 9 (10), 552. <https://doi.org/10.3390/biom9100552> Thakur, R., Pristijono, P., Bowyer, M., Singh, S. P., Scarlett, C. J., Stathopoulos, C. E., & Vuong, Q. V. (2019). A starch edible surface coating delays banana fruit ripening. *LWT*, 100, 341–347. <https://doi.org/10.1016/j.lwt.2018.10.055> Vallverdu-Queralt, A., Oms-Oliu, G., Odriozola-Serrano, I., Lamuela-Raventos, R. M., Martín-Belloso, O., & Elez-Martínez, P. (2012). Effects of pulsed electric fields on the bioactive compound content and antioxidant capacity of tomato fruit. *Journal of Agricultural and Food Chemistry*, 60(12), 3126–3134. <https://doi.org/10.1021/jf205216m> Wang, B., Xu, Y., Chen, L., Zhao, G., Mi, Z., Lv, D., & Niu, J. (2020). Optimizing the extraction of polysaccharides from *Bletilla ochracea* Schltr. using response surface methodology (RSM) and evaluating their antioxidant activity. *Processes*, 8(3), 341. <https://doi.org/10.3390/pr8030341> Wang, H., Zhang, Z., Xu, L., Huang, X., & Pang, X. (2012). The effect of delay between heat treatment and cold storage on alleviation of chilling injury in banana fruit. *Journal of the Science of Food and Agriculture*, 92(13), 2624–2629. <https://doi.org/10.1002/jsfa.5676> Wang, Y., Ji, S., Dai, H., Kong, X., Hao, J., Wang, S., ... Zhou, Q. (2019). Changes in membrane lipid metabolism accompany pitting in blueberry during refrigeration and subsequent storage at room temperature. *Frontiers in Plant Science*, 10, 829. <https://doi.org/10.3389/fpls.2019.00829> Wang, Y., Luo, Z., Du, R., Liu, Y., Ying, T., & Mao, L. (2013). Effect of nitric oxide on antioxidative response and proline metabolism in banana during cold storage. *Journal of Agricultural and Food Chemistry*, 61(37), 8880–8887. <https://doi.org/10.1021/jf401447y> Wellburn, A. R. (1994). The spectral determination of chlorophylls a and b, as well as total carotenoids, using various solvents with spectrophotometers of different resolution. *Journal of Plant Physiology*, 144(3), 307–313. [https://doi.org/10.1016/S0176-1617\(11\)81192-2](https://doi.org/10.1016/S0176-1617(11)81192-2) Zhang, W., Jiang, H., Cao, J., & Jiang, W. (2021). Advances in biochemical mechanisms and control technologies to treat chilling injury in postharvest fruits and vegetables. *Trends in Food Science & Technology*, 113, 355–365. <https://doi.org/10.1016/j.tifs.2021.05.009> Zhao, R., Hao, J., Xue, J., Liu, H., & Li, L. (2011). Effect of high-voltage electrostatic field pretreatment on the antioxidant system in stored green mature tomatoes. *Journal of the Science of Food and Agriculture*, 91(9), 1680–1686. <https://doi.org/10.1002/jsfa.4369> Zhong, K., Wu, J., Wang, Z., Chen, F., Liao, X., Hu, X., & Zhang, Z. (2007). Inactivation kinetics and secondary structural change of PEF-treated POD and PPO. *Food Chemistry*, 100(1), 115–123. <https://doi.org/10.1016/j.foodchem.2005.09.035> Zhu, Y., Wang, J., Vanga, S. K., & Raghavan, V. (2021). Visualizing structural changes of egg avidin to thermal and electric field stresses by molecular dynamics simulation. *LWT*, 151, Article 112139. <https://doi.org/10.1016/j.lwt.2021.112139> B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al.

3Food Packaging and Shelf Life 31 (2022)

) 100804 B.-K. Chen et al. Food Packaging and Shelf Life 31 (2022) 100804 2 3 4 5 6 7 8 9 10